

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | X F X 4 3 7 G E L            |
| 光源       | LED3000_85_2870 ×1 2870.0 lm |
| 管理番号     | K0192146 ( 0 ) D 1           |
| B Z 分類   | B Z 4                        |

| 器具効率   |       |           | 100 %           |           | 反射率             | 天井  | 80 %          |     |     |     | 70 % |     |     |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|-------|-----------|-----------------|-----------|-----------------|-----|---------------|-----|-----|-----|------|-----|-----|----|------|----|----|----|------|----|----|----|-----|
|        |       |           |                 |           |                 | 壁   | 70            | 50  | 30  | 10  | 70   | 50  | 30  | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |       |           |                 |           |                 | 床   | 10 %          |     |     |     | 10 % |     |     |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |       |           |                 |           |                 | 室指数 | 照明率 ( X0.01 ) |     |     |     |      |     |     |    |      |    |    |    |      |    |    |    |     |
| 保守率    |       |           | 良<br>中<br>否     | 0.81      | 0.6             | 59  | 48            | 40  | 35  | 58  | 47   | 40  | 35  | 56 | 46   | 40 | 35 | 54 | 45   | 39 | 35 | 33 |     |
|        |       |           |                 | 0.77      | 0.8             | 70  | 59            | 52  | 47  | 68  | 58   | 51  | 46  | 66 | 57   | 51 | 46 | 64 | 56   | 50 | 46 | 44 |     |
|        |       |           |                 | 0.68      | 1.0             | 77  | 67            | 60  | 55  | 75  | 66   | 60  | 54  | 73 | 65   | 59 | 54 | 70 | 63   | 58 | 54 | 52 |     |
|        |       |           |                 |           | 1.25            | 83  | 74            | 68  | 62  | 81  | 73   | 67  | 62  | 78 | 71   | 66 | 62 | 76 | 70   | 65 | 61 | 59 |     |
| 下方投影面積 |       |           | cm <sup>2</sup> | 1.5       | 87              | 79  | 73            | 68  | 85  | 78  | 72   | 68  | 82  | 76 | 71   | 67 | 80 | 75 | 70   | 67 | 64 |    |     |
|        |       |           |                 | 等価発光面積    | cm <sup>2</sup> | 2.0 | 92            | 86  | 80  | 76  | 91   | 85  | 80  | 76 | 88   | 83 | 78 | 75 | 85   | 81 | 77 | 74 | 72  |
| 取付高さ   |       | 器具間隔最大限   |                 |           | 2.5             | 95  | 90            | 85  | 81  | 94  | 89   | 85  | 81  | 91 | 87   | 83 | 80 | 88 | 85   | 82 | 79 | 77 |     |
|        |       | 横方向 ( A ) |                 | 縦方向 ( B ) | 3.0             | 97  | 93            | 89  | 85  | 96  | 92   | 88  | 85  | 93 | 90   | 86 | 84 | 91 | 88   | 85 | 83 | 80 |     |
| 1.5m   | 1.9 m | 2.12 m    | 4.0             | 100       | 97              | 93  | 90            | 99  | 95  | 92  | 90   | 96  | 93  | 91 | 88   | 94 | 91 | 89 | 87   | 85 |    |    |     |
| 2      | 2.52  | 2.66      | 5.0             | 102       | 99              | 96  | 94            | 100 | 98  | 95  | 93   | 98  | 96  | 93 | 91   | 95 | 94 | 92 | 90   | 87 |    |    |     |
| 2.5    | 3.13  | 3.23      | 7.0             | 104       | 101             | 99  | 98            | 102 | 100 | 98  | 97   | 100 | 98  | 97 | 95   | 97 | 96 | 95 | 93   | 91 |    |    |     |
| 3      | 3.74  | 3.81      | 10.0            | 105       | 104             | 102 | 101           | 104 | 102 | 101 | 100  | 101 | 100 | 99 | 98   | 99 | 98 | 97 | 96   | 93 |    |    |     |

