

屋内照明器具特性	
品番 (品名)	XS Z D 1 0 6 6 N
光源	L L D 2 4 1 0 N C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 2 0 2 8 (0) D B 1
B Z 分類	B Z 1

器具効率		8 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		8 4 %																				
保守率		良	0 . 6 7	0 . 6	7 8	7 5	7 2	7 1	7 8	7 4	7 2	7 1	7 7	7 4	7 2	7 1	7 6	7 4	7 2	7 1	7 0	
		中	0 . 6 3	0 . 8	8 1	7 8	7 6	7 5	8 1	7 8	7 6	7 5	8 0	7 7	7 6	7 4	7 9	7 7	7 5	7 4	7 3	
		否	0 . 5 6	1 . 0	8 3	8 1	7 9	7 7	8 3	8 0	7 8	7 7	8 2	8 0	7 8	7 7	8 1	7 9	7 8	7 6	7 6	
				1 . 2 5	8 5	8 3	8 1	7 9	8 4	8 2	8 0	7 9	8 3	8 1	8 0	7 9	8 2	8 1	7 9	7 8	7 7	
下方投影面積		c m ²		1 . 5	8 6	8 4	8 2	8 1	8 5	8 3	8 2	8 1	8 4	8 2	8 1	8 0	8 3	8 2	8 0	8 0	7 8	
等価発光面積		c m ²		2 . 0	8 7	8 6	8 4	8 3	8 7	8 5	8 4	8 3	8 5	8 4	8 3	8 2	8 4	8 3	8 2	8 1	8 0	
取付 高さ	器具間隔最大限		2 . 5	8 8	8 7	8 5	8 4	8 7	8 6	8 5	8 4	8 6	8 5	8 4	8 3	8 4	8 4	8 3	8 2	8 1		
	横方向 (A) 縦方向 (B)		3 . 0	8 9	8 7	8 6	8 5	8 8	8 7	8 6	8 5	8 6	8 5	8 5	8 4	8 5	8 4	8 3	8 3	8 1		
H m	0 . 8 0 H m	0 . 8 0 H m	4 . 0	8 9	8 8	8 7	8 7	8 8	8 8	8 7	8 6	8 7	8 6	8 5	8 5	8 5	8 5	8 4	8 4	8 2		
			5 . 0	9 0	8 9	8 8	8 8	8 9	8 8	8 7	8 7	8 7	8 7	8 6	8 6	8 6	8 5	8 5	8 4	8 2		
			7 . 0	9 0	9 0	8 9	8 9	8 9	8 9	8 8	8 8	8 8	8 7	8 7	8 6	8 6	8 6	8 5	8 5	8 3		
			1 0 . 0	9 1	9 0	9 0	8 9	9 0	8 9	8 9	8 9	8 8	8 8	8 7	8 7	8 6	8 6	8 6	8 6	8 3		

