

屋内照明器具特性	
品番 (品名)	XF X2 1 0 DEN
光源	LED5000_85_1600 ×1 1600.0 lm
管理番号	K0192925 (0) DB 1
B Z 分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z CM															
保守率		良 中 否	0.83	0.6	56	43	35	30	54	43	35	30	51	41	34	29	49	40	34	29	27	
			0.81	0.8	65	54	46	40	64	53	45	40	60	51	44	39	57	49	43	39	36	
			0.77	1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43	
				1.25	78	68	60	54	76	66	59	54	72	64	58	53	69	62	57	52	49	
下方投影面積		cm ²		1.5	82	73	65	60	80	71	65	59	76	69	63	58	73	66	61	57	54	
				2.0	87	80	73	68	85	78	72	67	82	75	70	66	78	73	69	65	62	
取付 高さ	器具間隔最大限			2.5	91	84	78	74	89	83	77	73	85	80	75	71	82	77	73	70	67	
	横方向 (A) 縦方向 (B)			3.0	93	87	82	78	91	86	81	77	88	83	79	75	84	80	77	74	70	
1.5m	1.93 m	1.91 m		4.0	97	92	88	84	95	90	86	83	91	87	84	81	88	84	82	79	75	
2	2.57	2.51		5.0	99	95	91	88	97	93	90	86	93	90	87	84	90	87	85	82	79	
2.5	3.21	3.11		7.0	101	98	95	92	99	96	94	91	96	93	91	89	92	90	88	87	83	
3	3.86	3.73		10.0	103	100	98	96	101	99	97	95	98	96	94	92	94	93	91	90	86	

