

屋内照明器具特性	
品番 (品名)	B Z 3
光源	F L R 4 0 S . W / M × 1 3 0 0 0 . 0 l m
管理番号	K 0 0 0 0 0 0 4 (4) D R 1
B Z 分類	B Z 3

器具効率	1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率	良 中 否	0 . 6	6 3	5 2	4 5	4 0	6 1	5 1	4 5	4 0	5 9	5 0	4 4	4 0	5 7	4 9	4 4	4 0	3 8		
		0 . 8	7 3	6 3	5 6	5 1	7 1	6 2	5 6	5 1	6 9	6 1	5 5	5 1	6 7	6 0	5 4	5 0	4 8		
		1 . 0	7 9	7 0	6 4	5 9	7 8	6 9	6 3	5 8	7 5	6 8	6 2	5 8	7 3	6 6	6 2	5 8	5 6		
下方投影面積		c m ²	1 . 2 5	8 5	7 7	7 1	6 6	8 3	7 6	7 0	6 6	8 1	7 4	6 9	6 5	7 8	7 3	6 8	6 5	6 3	
等価発光面積			c m ²	1 . 5	8 8	8 1	7 6	7 1	8 7	8 0	7 5	7 1	8 4	7 9	7 4	7 0	8 2	7 7	7 3	7 0	6 7
2 . 0	9 3		8 7	8 3	7 9	9 2	8 6	8 2	7 8	8 9	8 5	8 1	7 7	8 7	8 3	7 9	7 7	7 4			
取付 高さ	器具間隔最大限		2 . 5	9 6	9 1	8 7	8 4	9 5	9 0	8 6	8 3	9 2	8 8	8 5	8 2	9 0	8 7	8 4	8 1	7 9	
	横方向 (A) 縦方向 (B)		3 . 0	9 8	9 4	9 0	8 7	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	9 2	8 9	8 7	8 4	8 2	
H m	1 . 1 3 H m	1 . 1 3 H m	4 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 6	9 4	9 1	9 7	9 4	9 2	9 0	9 5	9 2	9 0	8 9	8 6	
			5 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 4	9 9	9 6	9 4	9 3	9 6	9 4	9 3	9 1	8 9	
			7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 4	9 2	
			1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 2	1 0 1	1 0 0	9 9	9 9	9 8	9 8	9 7	9 4	

