

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 2 5 B Z
光源	L D A 7 L - D - G / S / Z 6 × 1 8 1 0 . 0 l m
管理番号	K 0 1 5 5 0 5 5 (0) D B 1
B Z 分類	B Z 8

器具効率		8 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		3 5 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		4 9 %																					
保守率		良	0 . 6 3	0 . 6	3 8	2 7	2 1	1 6	3 5	2 5	1 9	1 5	3 0	2 2	1 7	1 3	2 5	1 8	1 4	1 1	7		
		中	0 . 6	0 . 8	4 5	3 5	2 7	2 2	4 2	3 2	2 6	2 1	3 5	2 8	2 2	1 8	2 9	2 3	1 9	1 6	1 1		
		否	0 . 5 6	1 . 0	5 0	4 0	3 3	2 7	4 6	3 7	3 1	2 6	3 9	3 2	2 7	2 2	3 3	2 7	2 3	1 9	1 3		
				1 . 2 5	5 5	4 5	3 8	3 3	5 1	4 2	3 6	3 1	4 3	3 6	3 1	2 7	3 6	3 1	2 6	2 3	1 6		
下方投影面積		c m ²		1 . 5	5 8	4 9	4 2	3 7	5 4	4 6	4 0	3 5	4 6	4 0	3 5	3 0	3 8	3 3	2 9	2 6	1 9		
等価発光面積		c m ²		2 . 0	6 3	5 5	4 9	4 4	5 8	5 2	4 6	4 1	5 0	4 4	4 0	3 6	4 2	3 8	3 4	3 1	2 3		
取付高さ	器具間隔最大限			2 . 5	6 6	5 9	5 3	4 9	6 1	5 5	5 0	4 6	5 3	4 8	4 4	4 0	4 4	4 1	3 7	3 4	2 5		
	横方向 (A)		縦方向 (B)	3 . 0	6 8	6 2	5 7	5 2	6 4	5 8	5 3	4 9	5 5	5 0	4 7	4 3	4 6	4 3	4 0	3 7	2 8		
H m	1 . 8 4 H m	1 . 8 3 H m	4 . 0	7 1	6 6	6 2	5 8	6 7	6 2	5 8	5 4	5 8	5 4	5 1	4 8	4 9	4 6	4 4	4 1	3 1			
			5 . 0	7 3	6 9	6 5	6 1	6 8	6 5	6 1	5 8	5 9	5 6	5 3	5 1	5 1	4 8	4 6	4 4	3 3			
			7 . 0	7 6	7 2	6 9	6 6	7 1	6 8	6 5	6 2	6 2	5 9	5 7	5 5	5 3	5 1	4 9	4 7	3 6			
			1 0 . 0	7 7	7 5	7 2	7 0	7 3	7 0	6 8	6 6	6 4	6 2	6 0	5 8	5 5	5 3	5 2	5 0	3 9			

