

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 4 7
光源	LDA4 L - H - E17 / E / S / W/ 2 × 1 440.0 l m
管理番号	K0185438 (0) DR 1
B Z 分類	BZ4 / 1.8 / BZ3

器具効率		5 2 %	反射率	天井	8 0 %					7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %					1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		5 2 %																					
保守率		良 中 否	0 . 6 7	0 . 6	3 1	2 4	2 0	1 8	3 0	2 4	2 0	1 8	2 9	2 4	2 0	1 8	2 8	2 3	2 0	1 8	1 7		
			0 . 6 3	0 . 8	3 6	3 1	2 7	2 4	3 5	3 0	2 7	2 4	3 4	3 0	2 6	2 4	3 3	2 9	2 6	2 4	2 3		
			0 . 5 6	1 . 0	4 0	3 5	3 1	2 8	3 9	3 4	3 1	2 8	3 8	3 4	3 1	2 8	3 6	3 3	3 0	2 8	2 7		
				1 . 2 5	4 3	3 9	3 5	3 3	4 2	3 8	3 5	3 2	4 1	3 7	3 4	3 2	4 0	3 6	3 4	3 2	3 1		
下方投影面積		c m ²	1 . 5	4 5	4 1	3 8	3 6	4 4	4 1	3 8	3 5	4 3	4 0	3 7	3 5	4 2	3 9	3 7	3 5	3 4			
等価発光面積		c m ²	2 . 0	4 8	4 5	4 2	4 0	4 7	4 4	4 2	4 0	4 6	4 3	4 1	3 9	4 4	4 2	4 0	3 9	3 8			
取付 高さ	器具間隔最大限		2 . 5	5 0	4 7	4 5	4 3	4 9	4 6	4 4	4 2	4 8	4 5	4 4	4 2	4 6	4 4	4 3	4 1	4 0			
	横方向 (A)		縦方向 (B)	3 . 0	5 1	4 9	4 7	4 5	5 0	4 8	4 6	4 4	4 9	4 7	4 5	4 4	4 7	4 6	4 5	4 3	4 2		
H m	1 . 3 4 H m	1 . 3 4 H m	4 . 0	5 2	5 0	4 9	4 7	5 2	5 0	4 8	4 7	5 0	4 9	4 8	4 6	4 9	4 8	4 7	4 6	4 4			
			5 . 0	5 3	5 2	5 0	4 9	5 2	5 1	5 0	4 9	5 1	5 0	4 9	4 8	5 0	4 9	4 8	4 7	4 6			
			7 . 0	5 4	5 3	5 2	5 1	5 3	5 2	5 1	5 1	5 2	5 1	5 0	5 0	5 1	5 0	5 0	4 9	4 7			
			1 0 . 0	5 5	5 4	5 3	5 3	5 4	5 3	5 3	5 2	5 3	5 2	5 2	5 1	5 2	5 1	5 1	5 0	4 9			

