

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 6 3
光源	L D A 4 W W - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 l m
管理番号	K 0 1 6 4 1 3 6 (1) D 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		5 3 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		2 % 5 1 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6	3 2	2 6	2 2	1 9	3 1	2 6	2 2	1 9	3 0	2 5	2 2	1 9	2 8	2 4	2 1	1 9	1 8	
			0 . 8	3 8	3 2	2 9	2 6	3 7	3 2	2 8	2 6	3 5	3 1	2 8	2 5	3 4	3 0	2 7	2 5	2 4	
			1 . 0	4 1	3 6	3 3	3 0	4 0	3 6	3 3	3 0	3 9	3 5	3 2	3 0	3 7	3 4	3 1	2 9	2 8	
			0 . 5 6	1 . 2 5	4 4	4 0	3 7	3 4	4 3	3 9	3 6	3 4	4 2	3 8	3 6	3 4	4 0	3 7	3 5	3 3	3 2
下方投影面積		c m ²	1 . 5	4 6	4 2	3 9	3 7	4 5	4 2	3 9	3 7	4 4	4 1	3 8	3 6	4 2	3 9	3 7	3 6	3 4	
等価発光面積		c m ²	2 . 0	4 9	4 6	4 3	4 1	4 8	4 5	4 3	4 1	4 6	4 4	4 2	4 0	4 5	4 3	4 1	3 9	3 8	
取付 高さ	器具間隔最大限		2 . 5	5 0	4 8	4 6	4 4	5 0	4 7	4 5	4 3	4 8	4 6	4 4	4 3	4 6	4 4	4 3	4 2	4 0	
	横方向 (A) 縦方向 (B)		3 . 0	5 2	4 9	4 7	4 6	5 1	4 9	4 7	4 5	4 9	4 7	4 6	4 4	4 7	4 6	4 5	4 3	4 2	
H m	1 . 3 8 H m	1 . 3 8 H m	4 . 0	5 3	5 1	5 0	4 8	5 2	5 0	4 9	4 8	5 0	4 9	4 8	4 7	4 9	4 7	4 6	4 6	4 4	
			5 . 0	5 4	5 2	5 1	5 0	5 3	5 1	5 0	4 9	5 1	5 0	4 9	4 8	4 9	4 8	4 8	4 7	4 5	
			7 . 0	5 5	5 3	5 2	5 2	5 4	5 3	5 2	5 1	5 2	5 1	5 0	5 0	5 0	5 0	4 9	4 8	4 6	
			1 0 . 0	5 5	5 4	5 4	5 3	5 4	5 4	5 3	5 2	5 3	5 2	5 2	5 1	5 1	5 1	5 0	5 0	4 8	

