

屋内照明器具特性	
品番 (品名)	L G B 1 6 0 7 7 Z
光源	LDA4 L - H - E17 / E / S / W/ 2 × 1 440.0 l m
管理番号	K0123326 (0) DB 1
BZ分類	BZ4 / 0.7 / BZ3

器具効率		75 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z C M																				
保守率		良 中 否	0.67	0.6	46	38	32	29	45	37	32	29	43	36	32	29	42	36	31	28	27				
			0.63	0.8	54	47	41	38	53	46	41	38	51	45	41	37	49	44	40	37	35				
			1.0	59	52	47	44	58	52	47	43	56	50	46	43	54	49	46	43	41					
			0.56	1.25	63	57	53	49	62	56	52	49	60	55	51	48	58	54	50	48	46				
下方投影面積		cm ²	1.5	66	60	56	53	65	60	56	53	62	58	55	52	60	57	54	51	50					
等価発光面積			2.0	70	65	61	58	68	64	61	58	66	63	60	57	64	61	59	56	54					
取付高さ	器具間隔最大限			2.5	72	68	65	62	71	67	64	62	68	65	63	61	66	64	62	60	58				
	横方向 (A)		縦方向 (B)	3.0	73	70	67	65	72	69	66	64	70	67	65	63	68	66	64	62	60				
H m	1.36 H m		1.36 H m	4.0	75	73	70	68	74	72	69	68	72	70	68	66	70	68	67	65	63				
				5.0	76	74	72	70	75	73	71	70	73	71	70	68	71	70	68	67	65				
				7.0	78	76	75	73	76	75	74	72	74	73	72	71	72	71	70	70	67				
				10.0	79	77	76	75	77	76	75	75	75	75	74	73	73	73	72	71	69				

