

屋内照明器具特性	
品番 (品名)	L G B 1 1 9 7 8
光源	LED2700_70_313 ×1 313.0 l m
管理番号	K0138375 (0) DB 1
B Z 分類	BZ7 / 0.7 / BZ6

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z C M																				
保守率		良 中 否	0.67	0.6	50	37	29	23	47	35	28	22	43	33	26	21	39	31	24	20	17				
			0.63	0.8	59	47	38	32	57	45	37	31	52	42	35	30	47	39	33	28	24				
			0.56	1.0	66	54	45	39	63	52	44	38	57	48	41	36	52	45	39	34	30				
				1.25	72	61	53	46	69	59	51	45	63	54	48	43	57	50	45	40	36				
下方投影面積		c m ²	1.5	76	66	58	52	73	64	56	50	67	59	53	48	61	55	50	45	40					
			2.0	82	73	66	60	79	71	64	59	72	66	60	55	66	61	56	52	47					
取付 高さ	器具間隔最大限		2.5	86	78	72	66	82	75	69	64	76	70	65	61	70	65	61	57	51					
	横方向 (A)	縦方向 (B)	3.0	88	82	76	71	85	79	73	69	78	73	69	65	72	68	65	61	55					
H m	1.04 H m	1.04 H m	4.0	92	86	81	77	88	83	79	75	82	78	74	71	76	73	69	67	60					
			5.0	94	89	85	81	91	86	82	79	84	81	77	74	78	75	73	70	63					
			7.0	97	93	90	86	93	90	87	84	87	84	82	79	81	79	77	75	67					
			10.0	99	96	93	91	95	93	91	88	89	87	85	83	83	81	80	78	71					

