

屋内照明器具特性	
品番 (品名)	L G B 5 2 6 9 4
光源	LED3500_70_2115 ×1 2115.0 l m
管理番号	K0140350 (1) DB 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		5 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		95 %																							
保守率		良 中 否	0.63	0.6	56	44	36	31	55	43	36	31	52	42	35	30	49	40	34	30	28				
			0.6	0.8	66	55	47	41	64	54	46	41	61	52	45	40	58	50	44	40	37				
			0.56	1.0	72	62	54	48	71	61	53	48	67	58	52	47	64	56	51	46	44				
				1.25	78	69	61	56	76	67	61	55	73	65	59	54	69	63	57	53	50				
下方投影面積		cm ²		1.5	82	74	67	61	80	72	66	61	76	70	64	59	73	67	62	58	55				
等価発光面積			cm ²	2.0	88	80	74	69	86	79	73	69	82	76	71	67	78	73	69	66	62				
取付 高さ	器具間隔最大限			2.5	91	85	80	75	89	83	78	74	85	80	76	72	82	78	74	71	67				
	横方向 (A)		縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	84	80	76	84	81	77	75	71				
H m	1.24 H m	1.24 H m		4.0	97	92	88	85	95	91	87	84	91	88	84	82	88	85	82	80	76				
				5.0	99	95	92	89	97	93	90	87	93	90	88	85	90	87	85	83	79				
				7.0	101	98	96	93	99	97	94	92	95	93	91	89	92	90	88	87	83				
				10.0	103	101	99	97	101	99	97	95	97	96	94	93	94	93	91	90	86				

