

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 1 6
光源	LED2700_70_270 ×1 270.0 lm
管理番号	K0150803 (0) DB 1
B Z 分類	BZ2 / 1.1 / BZ3

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		8 % 92 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.67	0.6	65	55	49	45	64	55	49	44	61	53	48	44	59	52	47	43	41	
			0.63	0.8	74	65	59	54	72	64	58	54	69	62	57	53	66	60	56	52	50	
			0.56	1.0	80	71	65	61	78	70	65	60	74	68	63	59	71	66	62	58	56	
				1.25	84	77	71	67	83	76	70	66	79	73	69	65	76	71	67	64	61	
下方投影面積 等価発光面積		cm ² cm ²		1.5	88	81	76	71	86	79	75	71	82	77	73	69	79	74	71	68	64	
				2.0	92	86	82	78	90	85	80	77	86	82	78	75	83	79	76	73	70	
取付 高さ	器具間隔最大限			2.5	95	90	86	82	93	88	84	81	89	85	82	79	85	82	79	77	73	
	横方向 (A) 縦方向 (B)			3.0	97	92	89	85	94	91	87	84	91	87	84	82	87	84	82	80	76	
H m	1.29 H m	1.29 H m		4.0	99	95	92	90	97	94	91	88	93	90	88	86	89	87	85	83	79	
				5.0	100	98	95	93	98	96	93	91	94	92	90	88	91	89	87	86	81	
				7.0	102	100	98	96	100	98	96	94	96	94	93	91	92	91	90	89	84	
				10.0	103	102	100	99	101	100	98	97	97	96	95	94	94	93	92	91	86	

