

屋内照明器具特性	
品番 (品名)	L G B 8 7 0 2 1 Z
光源	LDA4 L - H - E17 / E / S / W/ 2 ×1 440.0 l m
管理番号	K0123366 (0) DB 1
B Z 分類	BZ10

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	35	25	19	15	31	23	17	13	24	17	13	10	17	12	9	7	1
			0.6	0.8	42	32	25	21	37	28	23	18	28	22	17	14	20	15	12	10	3
			0.56	1.0	46	37	30	25	41	33	27	23	31	25	21	17	22	18	15	12	4
				1.25	51	42	35	30	45	37	32	27	34	29	24	21	24	20	17	15	5
下方投影面積		cm ²		1.5	54	46	39	34	48	41	35	31	37	31	27	24	26	22	19	17	6
			等価発光面積	cm ²	2.0	58	51	45	41	52	46	41	36	40	35	32	28	29	25	23	20
取付 高さ	器具間隔最大限			2.5	61	55	50	45	55	49	45	41	42	38	35	32	31	28	25	23	9
	横方向 (A) 縦方向 (B)			3.0	63	58	53	49	57	52	47	44	44	40	37	34	32	29	27	25	11
H m	0.00 H m	1.83 H m		4.0	66	61	57	54	59	55	52	48	46	43	40	38	34	32	30	28	13
				5.0	68	64	60	57	61	57	54	51	48	45	43	40	35	33	31	30	14
				7.0	70	67	64	61	63	60	58	55	50	48	46	44	37	35	34	32	16
				10.0	72	69	67	65	65	63	61	59	51	50	48	47	38	37	36	35	18

