

屋内照明器具特性	
品番 (品名)	LGB87061K
光源	LDA3L-H-E17/25E/W ×1 360.0 l m
管理番号	K0123531 (1) DB 1
BZ分類	BZ5/2.3/BZ6

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		28 %	室指数	照明率 (X0.01)																		Z	CM
下方光束		55 %																					
保守率		良 中 否	0.67	0.6	43	34	28	23	41	32	26	23	36	29	24	21	32	26	22	19	16		
			0.63	0.8	50	41	35	30	47	39	33	29	42	35	30	27	37	32	28	25	20		
			0.56	1.0	55	46	40	35	52	44	38	34	46	39	35	31	40	35	31	28	23		
				1.25	59	51	45	40	56	49	43	39	49	44	39	35	44	39	35	32	27		
下方投影面積		cm ²	1.5	62	55	49	44	59	52	47	42	52	47	42	39	46	42	38	35	29			
等価発光面積			cm ²	2.0	67	60	55	50	63	57	52	48	56	51	47	44	49	46	43	40	33		
取付 高さ	器具間隔最大限		2.5	69	64	59	55	66	60	56	52	58	54	51	48	52	48	46	43	36			
	横方向 (A)		縦方向 (B)	3.0	71	66	62	58	68	63	59	56	60	57	53	51	53	50	48	46	38		
H m	0.89 H m		1.36 H m	4.0	74	70	66	63	70	66	63	60	63	60	57	54	56	53	51	49	41		
				5.0	76	72	69	66	72	68	66	63	64	62	59	57	57	55	53	51	43		
				7.0	78	75	72	70	74	71	69	67	66	64	62	60	59	57	56	54	45		
				10.0	79	77	75	73	75	73	72	70	68	66	65	63	60	59	58	57	48		

