

屋内照明器具特性	
品番 (品名)	L G B C 5 5 0 0 5
光源	LED2700_70_378 ×1 378.0 l m
管理番号	K0172980 (0) DR 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		2 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		98 %																						
保守率		良 中 否	0.67	0.6	57	45	37	32	56	44	37	32	53	43	36	32	51	42	36	31	29			
			0.63	0.8	67	55	48	42	65	55	47	42	62	53	46	41	60	52	46	41	39			
			0.56	1.0	73	63	55	49	72	62	55	49	68	60	54	49	66	58	53	48	46			
				1.25	79	70	62	57	77	68	62	56	74	66	60	56	71	64	59	55	52			
下方投影面積		cm ²	1.5	83	74	68	62	81	73	67	62	78	71	65	61	75	69	64	60	57				
			等価発光面積		cm ²	2.0	89	81	75	70	87	80	74	70	83	78	73	69	80	75	71	68	65	
取付	器具間隔最大限			2.5	92	86	80	76	90	84	79	75	87	82	78	74	84	80	76	73	70			
高さ	横方向 (A)		縦方向 (B)	3.0	95	89	84	80	93	88	83	79	89	85	81	78	86	83	79	76	73			
H m	1.22 H m	1.22 H m	4.0	98	93	89	86	96	92	88	85	93	89	86	83	90	87	84	82	78				
			5.0	100	96	92	89	98	94	91	88	95	92	89	87	92	89	87	85	82				
			7.0	102	99	96	94	100	98	95	93	97	95	93	91	94	92	90	89	85				
			10.0	103	101	99	98	102	100	98	96	99	97	96	94	96	95	93	92	89				

