

屋内照明器具特性	
品番 (品名)	L G B C 8 1 0 4 3
光源	LED2700_70_1410 ×1 1410.0 l m
管理番号	K0147588 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5 / 3.5 / BZ6

器具効率		1 0 0 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
					室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 3	4 1	3 3	2 7	5 2	4 0	3 2	2 7	4 8	3 8	3 1	2 6	4 5	3 6	3 0	2 6	2 3	
			0 . 6	0 . 8	6 3	5 1	4 2	3 6	6 1	5 0	4 2	3 6	5 7	4 7	4 0	3 5	5 3	4 5	3 9	3 4	3 1	
			0 . 5 6	1 . 0	6 9	5 8	5 0	4 3	6 7	5 6	4 9	4 3	6 3	5 4	4 7	4 2	5 9	5 1	4 5	4 1	3 7	
				1 . 2 5	7 5	6 4	5 7	5 0	7 3	6 3	5 5	5 0	6 8	6 0	5 3	4 8	6 4	5 7	5 2	4 7	4 3	
下方投影面積		c m ²	1 . 5	7 9	6 9	6 2	5 6	7 7	6 8	6 1	5 5	7 2	6 4	5 8	5 3	6 8	6 1	5 6	5 2	4 8		
			等価発光面積	2 . 0	8 5	7 6	7 0	6 4	8 2	7 5	6 8	6 3	7 7	7 1	6 6	6 1	7 3	6 8	6 3	5 9	5 5	
取付高さ	器具間隔最大限			2 . 5	8 8	8 1	7 5	7 0	8 6	7 9	7 3	6 8	8 1	7 5	7 1	6 6	7 7	7 2	6 8	6 4	6 0	
	横方向 (A)		縦方向 (B)	3 . 0	9 1	8 4	7 9	7 4	8 8	8 2	7 7	7 3	8 4	7 9	7 4	7 0	7 9	7 5	7 1	6 8	6 3	
H m	1 . 2 9 H m		1 . 2 9 H m	4 . 0	9 4	8 9	8 4	8 0	9 2	8 7	8 3	7 9	8 7	8 3	7 9	7 6	8 3	7 9	7 6	7 3	6 8	
				5 . 0	9 6	9 2	8 8	8 4	9 4	9 0	8 6	8 3	8 9	8 6	8 3	8 0	8 5	8 2	7 9	7 7	7 2	
				7 . 0	9 9	9 5	9 2	8 9	9 6	9 3	9 0	8 7	9 2	8 9	8 7	8 4	8 8	8 5	8 3	8 1	7 6	
				1 0 . 0	1 0 1	9 8	9 6	9 3	9 8	9 6	9 4	9 2	9 4	9 2	9 0	8 8	9 0	8 8	8 6	8 5	8 0	

