

屋内照明器具特性

品番 (品名)	L G W 4 5 5 0 4 B F																		
光源	L D A 4 L - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 l m																		
管理番号	K 0 1 5 8 8 5 5 (0) D B 1																		
B Z 分類	B Z 1 0																		

器具効率 上方光束 下方光束		4 6 % 2 2 % 2 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 9	0 . 6	1 9	1 3	9	7	1 8	1 2	9	6	1 4	1 0	7	5	1 1	8	5	4	1
			0 . 6 7	0 . 8	2 3	1 7	1 3	1 0	2 1	1 5	1 2	9	1 7	1 3	1 0	7	1 3	1 0	7	6	2
			0 . 6 3	1 . 0	2 6	2 0	1 6	1 2	2 3	1 8	1 4	1 1	1 9	1 5	1 2	9	1 5	1 2	9	7	4
				1 . 2 5	2 8	2 3	1 9	1 5	2 6	2 1	1 7	1 4	2 1	1 7	1 4	1 1	1 6	1 3	1 1	9	5
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	3 0	2 5	2 1	1 8	2 7	2 3	1 9	1 6	2 2	1 9	1 6	1 3	1 8	1 5	1 3	1 1	6	
			2 . 0	3 3	2 8	2 5	2 1	3 0	2 6	2 3	2 0	2 5	2 1	1 9	1 6	2 0	1 7	1 5	1 3	8	
取付 高さ	器具間隔最大限		2 . 5	3 5	3 1	2 7	2 4	3 2	2 8	2 5	2 2	2 6	2 3	2 1	1 9	2 1	1 9	1 7	1 5	9	
	横方向 (A) 縦方向 (B)		3 . 0	3 6	3 2	2 9	2 6	3 3	3 0	2 7	2 4	2 7	2 5	2 2	2 0	2 2	2 0	1 8	1 7	1 1	
H m	0 . 0 0 H m 0 . 0 0 H m		4 . 0	3 8	3 5	3 2	2 9	3 5	3 2	2 9	2 7	2 9	2 7	2 5	2 3	2 4	2 2	2 0	1 9	1 2	
			5 . 0	3 9	3 6	3 4	3 1	3 6	3 3	3 1	2 9	3 0	2 8	2 6	2 5	2 5	2 3	2 2	2 0	1 4	
			7 . 0	4 0	3 8	3 6	3 4	3 7	3 5	3 4	3 2	3 1	3 0	2 8	2 7	2 6	2 5	2 4	2 2	1 6	
			1 0 . 0	4 1	4 0	3 8	3 7	3 8	3 7	3 5	3 4	3 3	3 1	3 0	2 9	2 7	2 6	2 5	2 4	1 7	

