

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 4 0 A Z
光源	L D A 4 L - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 l m
管理番号	K 0 1 2 5 0 9 4 (3) D B 1
B Z 分類	B Z 7

器具効率		49 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		25 %	室指数	照明率 (X0.01)																	Z	CM
下方光束		24 %																				
保守率		良 中 否	0.63	0.6	2.2	1.6	1.3	1.0	2.0	1.5	1.2	0.9	1.7	1.3	1.0	0.8	1.3	1.0	0.8	0.6	0.4	
			0.6	0.8	2.7	2.1	1.7	1.4	2.4	1.9	1.6	1.3	2.0	1.6	1.3	1.1	1.6	1.3	1.1	0.9	0.6	
			0.56	1.0	2.9	2.4	2.0	1.7	2.7	2.2	1.9	1.6	2.2	1.8	1.6	1.3	1.8	1.5	1.3	1.1	0.7	
				1.25	3.2	2.7	2.3	2.0	2.9	2.5	2.2	1.9	2.4	2.1	1.8	1.6	2.0	1.7	1.5	1.3	0.9	
下方投影面積		cm ²		1.5	3.4	2.9	2.6	2.3	3.1	2.7	2.4	2.1	2.6	2.3	2.0	1.8	2.1	1.9	1.7	1.5	1.0	
等価発光面積		cm ²		2.0	3.7	3.3	2.9	2.7	3.4	3.0	2.7	2.5	2.8	2.5	2.3	2.1	2.3	2.1	1.9	1.7	1.2	
取付 高さ	器具間隔最大限			2.5	3.8	3.5	3.2	2.9	3.5	3.2	3.0	2.7	3.0	2.7	2.5	2.3	2.4	2.2	2.1	1.9	1.3	
	横方向 (A)		縦方向 (B)	3.0	4.0	3.7	3.4	3.1	3.7	3.4	3.1	2.9	3.1	2.8	2.7	2.5	2.5	2.3	2.2	2.1	1.4	
H m	1.24 H m		1.89 H m	4.0	4.1	3.9	3.6	3.4	3.8	3.6	3.4	3.2	3.2	3.0	2.9	2.7	2.6	2.5	2.4	2.3	1.6	
				5.0	4.2	4.0	3.8	3.6	3.9	3.7	3.5	3.4	3.3	3.1	3.0	2.9	2.7	2.6	2.5	2.4	1.7	
				7.0	4.4	4.2	4.0	3.9	4.0	3.9	3.7	3.6	3.4	3.3	3.2	3.1	2.8	2.7	2.6	2.6	1.8	
				10.0	4.5	4.3	4.2	4.1	4.1	4.0	3.9	3.8	3.5	3.4	3.3	3.2	2.9	2.8	2.8	2.7	1.9	

