

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 7 0 U
光源	LDA4 L - H - E17 / E / S / W / 2 × 1 440.0 l m
管理番号	K0125807 (1) DB 1
BZ分類	BZ10 / 0.7 / BZ9

器具効率		48 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		21 % 27 %	室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.63	0.6	21	15	11	8	19	13	10	7	16	11	8	6	13	9	7	5	2
			0.6	0.8	25	19	14	11	23	17	13	10	19	14	11	9	15	12	9	7	4
			0.56	1.0	28	22	17	14	25	20	16	13	21	17	14	11	17	14	11	9	5
			1.25	30	25	20	17	28	23	19	16	23	19	16	13	19	16	13	11	7	
下方投影面積		cm ²	1.5	32	27	23	20	30	25	21	18	25	21	18	15	20	17	15	13	8	
等価発光面積			2.0	35	30	27	23	32	28	25	22	27	24	21	19	22	20	17	16	10	
取付 高さ	器具間隔最大限		2.5	37	33	29	26	34	30	27	25	29	26	23	21	24	21	19	18	12	
	横方向 (A) 縦方向 (B)		3.0	38	35	31	29	35	32	29	27	30	27	25	23	25	23	21	19	13	
H m	0.00 H m	1.46 H m	4.0	40	37	34	32	37	34	32	30	32	29	27	26	26	25	23	22	15	
			5.0	41	39	36	34	38	36	34	32	33	31	29	27	27	26	24	23	17	
			7.0	43	41	39	37	40	38	36	34	34	33	31	30	29	27	26	25	19	
			10.0	44	42	41	39	41	39	38	37	35	34	33	32	30	29	28	27	20	

