

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 7 1 U
光源	L D A 4 L - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 l m
管理番号	K 0 1 2 5 8 0 1 (1) D B 1
B Z 分類	B Z 1 0 / 0 . 7 / B Z 9

器具効率		3 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 4 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		1 8 %																					
保守率		良 中 否	0 . 6 3	0 . 6	1 4	9	7	5	1 2	9	6	5	1 0	7	5	4	8	6	4	3	2		
			0 . 6	0 . 8	1 6	1 2	9	7	1 5	1 1	9	7	1 2	9	7	6	1 0	8	6	5	3		
				1 . 0	1 8	1 4	1 1	9	1 7	1 3	1 0	8	1 4	1 1	9	7	1 1	9	7	6	4		
			0 . 5 6	1 . 2 5	2 0	1 6	1 3	1 1	1 8	1 5	1 2	1 0	1 5	1 3	1 0	9	1 2	1 0	9	7	5		
下方投影面積		c m ²	1 . 5	2 1	1 8	1 5	1 3	1 9	1 6	1 4	1 2	1 6	1 4	1 2	1 0	1 3	1 1	1 0	8	6			
等価発光面積		c m ²	2 . 0	2 3	2 0	1 7	1 5	2 1	1 8	1 6	1 4	1 8	1 6	1 4	1 2	1 5	1 3	1 2	1 0	7			
取付 高さ	器具間隔最大限		2 . 5	2 4	2 1	1 9	1 7	2 2	2 0	1 8	1 6	1 9	1 7	1 5	1 4	1 6	1 4	1 3	1 2	8			
	横方向 (A)		縦方向 (B)	3 . 0	2 5	2 3	2 0	1 9	2 3	2 1	1 9	1 7	2 0	1 8	1 6	1 5	1 7	1 5	1 4	1 3	9		
H m	0 . 0 0 H m	1 . 4 4 H m	4 . 0	2 6	2 4	2 2	2 1	2 4	2 3	2 1	1 9	2 1	1 9	1 8	1 7	1 8	1 6	1 5	1 4	1 0			
			5 . 0	2 7	2 5	2 4	2 2	2 5	2 4	2 2	2 1	2 2	2 0	1 9	1 8	1 8	1 7	1 6	1 5	1 1			
			7 . 0	2 8	2 7	2 5	2 4	2 6	2 5	2 4	2 3	2 3	2 2	2 1	2 0	1 9	1 8	1 8	1 7	1 3			
			1 0 . 0	2 9	2 8	2 7	2 6	2 7	2 6	2 5	2 4	2 3	2 3	2 2	2 1	2 0	1 9	1 9	1 8	1 4			

