

屋内照明器具特性	
品番 (品名)	NNF 4 1 2 4 5 C
光源	LDL40S . N / 19 / 25 - K ×1 2500.0 lm
管理番号	K0126618 (*) DB 1
BZ分類	BZ6

器具効率	96 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	3 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	93 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.81 0.77 0.68	0.6	51	39	31	25	50	38	31	25	47	37	30	25	44	35	29	25	22	
		0.8	60	49	40	34	59	48	40	34	55	46	39	34	53	44	38	33	31	
		1.0	67	55	47	41	65	54	47	41	61	52	45	40	58	50	44	39	37	
		1.25	72	62	54	48	70	61	53	47	67	58	52	47	63	56	50	46	43	
下方投影面積	c m ²	1.5	76	67	59	53	74	65	58	53	70	63	57	52	67	61	55	51	48	
		2.0	82	73	67	61	80	72	66	60	76	69	64	59	72	67	62	58	55	
取付高さ	器具間隔最大限		2.5	85	78	72	67	83	77	71	66	80	74	69	65	76	71	67	63	60
	横方向 (A)	縦方向 (B)	3.0	88	81	76	71	86	80	75	70	82	77	73	69	79	74	71	67	64
1.5m	2.07 m	2.13 m	4.0	91	86	81	77	89	84	80	76	86	81	78	74	82	79	75	73	69
2	2.73	2.69	5.0	93	89	85	81	91	87	83	80	88	84	81	78	84	81	79	76	73
2.5	3.39	3.27	7.0	96	92	89	86	94	91	88	85	90	88	85	83	87	85	83	81	77
3	4.04	3.86	10.0	98	95	93	90	96	94	91	89	93	91	89	87	89	88	86	84	81

