

屋内照明器具特性	
品番 (品名)	NNF 4 2 5 9 1
光源	LDL40S. N/ 14 / 26 (2 6 0 0 A) × 2 2 6 0 0 . 0 l m
管理番号	K0126407 (0) DB 1
B Z 分類	BZ5 / 0 . 7 / BZ4

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		3 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		88 %																						
保守率		良 中 否	0.81	0.6	52	41	34	29	51	40	34	29	48	39	33	29	46	38	33	29	27			
			0.77	0.8	61	51	44	39	60	50	44	39	57	49	43	39	55	48	42	38	36			
			1.0	68	58	52	47	66	57	51	46	63	56	50	46	60	54	49	45	43				
			0.68	1.25	73	65	58	54	71	64	58	53	68	62	57	53	66	60	56	52	49			
下方投影面積		cm ²	1.5	77	69	63	59	75	68	63	58	72	66	61	57	69	64	60	57	54				
等価発光面積		cm ²	2.0	82	76	70	66	80	74	70	66	77	72	68	65	74	70	67	64	61				
取付 高さ	器具間隔最大限		2.5	85	80	75	71	83	78	74	71	80	76	72	69	77	74	71	68	65				
	横方向 (A) 縦方向 (B)		3.0	87	82	78	75	85	81	77	74	82	79	76	73	79	76	74	71	69				
1.5m	2.08 m	2.18 m	4.0	90	86	83	80	88	85	82	79	85	82	80	77	82	80	78	76	73				
2	2.75	2.75	5.0	91	88	86	83	90	87	84	82	87	84	82	80	84	82	80	79	76				
2.5	3.42	3.34	7.0	93	91	89	87	92	89	88	86	89	87	85	84	86	85	83	82	79				
3	4.08	3.94	10.0	94	93	91	90	93	91	90	89	90	89	88	87	87	86	86	85	81				

