

屋内照明器具特性	
品番 (品名)	N N F W2 1 8 6 1
光源	LDL20S. N/11/12-K(960) ×1 960.0 l m
管理番号	K0125171 (0) DR 1
B Z 分類	B Z 8

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		36 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		35 %																					
保守率		良 中 否	0.77	0.6	32	23	18	14	29	22	17	13	24	18	14	11	19	15	11	9	5		
			0.72	0.8	38	29	24	19	35	27	22	18	29	23	19	15	23	19	15	13	8		
			1.0	42	34	28	24	38	31	26	22	32	26	22	19	26	21	18	15	10			
			0.68	1.25	46	38	33	28	42	35	30	26	35	30	25	22	28	24	21	18	12		
下方投影面積		cm ²	1.5	49	42	36	32	45	38	33	29	37	32	28	25	30	26	23	21	14			
			等価発光面積		cm ²	2.0	53	46	41	37	48	43	38	35	40	36	32	29	33	30	27	24	16
取付 高さ	器具間隔最大限		2.5	55	50	45	41	51	46	42	38	42	39	35	33	35	32	29	27	18			
	横方向 (A) 縦方向 (B)		3.0	57	52	48	44	52	48	44	41	44	41	38	35	36	33	31	29	20			
1.5m	2.14 m	1.86 m	4.0	59	55	52	48	55	51	48	45	46	43	41	38	38	36	34	32	22			
2	2.85	2.45	5.0	61	57	54	51	56	53	50	48	48	45	43	41	39	37	36	34	24			
2.5	3.56	3.04	7.0	63	60	57	55	58	56	53	51	49	47	46	44	41	39	38	37	26			
3	4.26	3.63	10.0	64	62	60	58	60	58	56	54	51	49	48	47	42	41	40	39	28			

