

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NTN81330+NTN81997            |
| 光源       | LED5000_70_1350 ×1 1350.0 lm |
| 管理番号     | K0163041 ( 0 ) DR 1          |
| BZ分類     | BZ5                          |

| 器具効率   |        | 100 %           | 反射率  | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |   |   |  |   |
|--------|--------|-----------------|------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|---|---|--|---|
|        |        |                 |      | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |   |  |   |
|        |        |                 |      | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |   |   |  |   |
| 上方光束   |        | 12 %            | 室指数  | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z | C |  | M |
| 下方光束   |        | 88 %            |      |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |   |   |  |   |
| 保守率    |        | 良<br>中<br>否     | 0.69 | 0.6           | 53   | 41 | 33 | 28 | 52   | 40 | 32 | 27 | 48   | 38 | 31 | 26 | 45   | 36 | 30 | 26 | 23  |   |   |  |   |
|        |        |                 | 0.67 | 0.8           | 63   | 51 | 43 | 37 | 61   | 50 | 42 | 37 | 57   | 47 | 40 | 35 | 53   | 45 | 39 | 34 | 31  |   |   |  |   |
|        |        |                 | 0.63 | 1.0           | 69   | 58 | 50 | 44 | 67   | 57 | 49 | 43 | 62   | 54 | 47 | 42 | 58   | 51 | 45 | 41 | 37  |   |   |  |   |
|        |        |                 |      | 1.25          | 75   | 65 | 57 | 51 | 73   | 63 | 56 | 50 | 68   | 60 | 54 | 49 | 63   | 57 | 51 | 47 | 43  |   |   |  |   |
| 下方投影面積 |        | cm <sup>2</sup> | 1.5  | 79            | 70   | 62 | 56 | 77 | 68   | 61 | 55 | 72 | 64   | 58 | 54 | 67 | 61   | 56 | 52 | 47 |     |   |   |  |   |
|        |        |                 | 2.0  | 85            | 77   | 70 | 65 | 82 | 75   | 69 | 63 | 77 | 71   | 66 | 61 | 72 | 67   | 63 | 59 | 54 |     |   |   |  |   |
| 等価発光面積 |        | cm <sup>2</sup> | 2.5  | 88            | 81   | 75 | 70 | 86 | 79   | 74 | 69 | 80 | 75   | 70 | 66 | 76 | 71   | 67 | 64 | 59 |     |   |   |  |   |
|        |        |                 | 3.0  | 91            | 85   | 79 | 75 | 88 | 82   | 77 | 73 | 83 | 78   | 74 | 70 | 78 | 74   | 71 | 68 | 62 |     |   |   |  |   |
| 1.5m   | 1.98 m | 1.97 m          | 4.0  | 94            | 89   | 85 | 81 | 91 | 87   | 83 | 79 | 86 | 82   | 79 | 76 | 81 | 78   | 75 | 73 | 67 |     |   |   |  |   |
| 2      | 2.62   | 2.55            | 5.0  | 96            | 92   | 88 | 84 | 94 | 90   | 86 | 83 | 88 | 85   | 82 | 79 | 83 | 81   | 78 | 76 | 70 |     |   |   |  |   |
| 2.5    | 3.27   | 3.15            | 7.0  | 99            | 95   | 92 | 89 | 96 | 93   | 90 | 88 | 91 | 88   | 86 | 84 | 86 | 84   | 82 | 80 | 74 |     |   |   |  |   |
| 3      | 3.92   | 3.75            | 10.0 | 101           | 98   | 96 | 94 | 98 | 96   | 94 | 92 | 93 | 91   | 89 | 88 | 88 | 87   | 85 | 84 | 78 |     |   |   |  |   |

