

| 屋内照明器具特性 |                        |
|----------|------------------------|
| 品番 (品名)  | NTN88006B              |
| 光源       | LLD3020CU1 ×1 615.0 lm |
| 管理番号     | K0181913 (0) DR1       |
| BZ分類     | BZ1                    |

| 器具効率     |           | 83 %             | 反<br>射<br>率      | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |   |   |   |
|----------|-----------|------------------|------------------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|---|---|---|
|          |           |                  |                  | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |   |   |
|          |           |                  |                  | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |   |   |   |
| 上方光束     |           | 0 %              | 室指数              | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z | C | M |
| 下方光束     |           | 83 %             |                  |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |   |   |   |
| 保守率      |           | 良<br>中<br>否      | 0.67             | 0.6           | 71   | 66 | 63 | 61 | 70   | 66 | 63 | 61 | 69   | 65 | 62 | 61 | 68   | 65 | 62 | 60 | 60  |   |   |   |
|          |           |                  | 0.63             | 0.8           | 75   | 71 | 68 | 66 | 74   | 71 | 68 | 66 | 73   | 70 | 67 | 65 | 72   | 69 | 67 | 65 | 64  |   |   |   |
|          |           |                  | 0.56             | 1.0           | 78   | 74 | 71 | 69 | 77   | 74 | 71 | 69 | 76   | 73 | 71 | 69 | 75   | 72 | 70 | 69 | 67  |   |   |   |
|          |           |                  |                  | 1.25          | 80   | 77 | 74 | 72 | 80   | 76 | 74 | 72 | 78   | 76 | 73 | 72 | 77   | 75 | 73 | 71 | 70  |   |   |   |
| 下方投影面積   |           | c m <sup>2</sup> | 1.5              | 82            | 79   | 77 | 75 | 81 | 78   | 76 | 74 | 80 | 77   | 75 | 74 | 78 | 76   | 75 | 73 | 72 |     |   |   |   |
| 等価発光面積   |           |                  | c m <sup>2</sup> | 2.0           | 84   | 81 | 79 | 78 | 83   | 81 | 79 | 77 | 81   | 80 | 78 | 77 | 80   | 78 | 77 | 76 | 75  |   |   |   |
| 取付<br>高さ | 器具間隔最大限   |                  | 2.5              | 85            | 83   | 81 | 80 | 84 | 82   | 81 | 79 | 83 | 81   | 80 | 79 | 81 | 80   | 79 | 78 | 76 |     |   |   |   |
|          | 横方向 ( A ) |                  | 縦方向 ( B )        | 3.0           | 86   | 84 | 83 | 81 | 85   | 83 | 82 | 81 | 83   | 82 | 81 | 80 | 82   | 81 | 80 | 79 | 77  |   |   |   |
| H m      | 0.36 H m  | 0.36 H m         | 4.0              | 87            | 85   | 84 | 83 | 86 | 85   | 84 | 83 | 84 | 83   | 82 | 81 | 83 | 82   | 81 | 80 | 78 |     |   |   |   |
|          |           |                  | 5.0              | 87            | 86   | 85 | 84 | 87 | 86   | 85 | 84 | 85 | 84   | 83 | 82 | 83 | 82   | 82 | 81 | 79 |     |   |   |   |
|          |           |                  | 7.0              | 88            | 87   | 86 | 86 | 87 | 86   | 86 | 85 | 85 | 85   | 84 | 84 | 84 | 83   | 83 | 82 | 80 |     |   |   |   |
|          |           |                  | 10.0             | 89            | 88   | 87 | 87 | 88 | 87   | 87 | 86 | 86 | 85   | 85 | 85 | 84 | 84   | 83 | 83 | 81 |     |   |   |   |

