

屋内照明器具特性	
品番 (品名)	YK34780Z
光源	HF400X/N ×1 22000.0 lm
管理番号	K0114615(0)DB1
BZ分類	BZ3/0.7/BZ2

器具効率	75%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	75%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.69 0.65 0.61	0.6	4.9	4.1	3.6	3.3	4.8	4.1	3.6	3.3	4.7	4.0	3.6	3.3	4.5	4.0	3.6	3.3	3.2	
		0.8	5.7	5.0	4.5	4.2	5.6	4.9	4.5	4.2	5.4	4.8	4.4	4.2	5.2	4.8	4.4	4.1	4.0	
		1.0	6.1	5.5	5.1	4.8	6.0	5.5	5.1	4.8	5.9	5.4	5.0	4.7	5.7	5.3	5.0	4.7	4.6	
		1.25	6.5	6.0	5.6	5.3	6.4	5.9	5.6	5.3	6.2	5.8	5.5	5.2	6.1	5.7	5.4	5.2	5.1	
下方投影面積	c m ²	1.5	6.8	6.3	5.9	5.6	6.7	6.2	5.9	5.6	6.5	6.1	5.8	5.6	6.3	6.0	5.7	5.5	5.4	
		2.0	7.1	6.7	6.4	6.1	7.0	6.6	6.4	6.1	6.8	6.5	6.3	6.1	6.6	6.4	6.2	6.0	5.8	
取付高さ	器具間隔最大限		2.5	7.3	7.0	6.7	6.5	7.2	6.9	6.6	6.4	7.0	6.8	6.5	6.4	6.8	6.6	6.4	6.3	6.1
	横方向 (A)	縦方向 (B)	3.0	7.4	7.1	6.9	6.7	7.3	7.1	6.9	6.7	7.1	6.9	6.7	6.6	7.0	6.8	6.6	6.5	6.3
H m	1.24 H m	1.24 H m	4.0	7.6	7.4	7.2	7.0	7.5	7.3	7.1	7.0	7.3	7.1	7.0	6.9	7.1	7.0	6.9	6.8	6.6
			5.0	7.7	7.5	7.3	7.2	7.6	7.4	7.3	7.1	7.4	7.3	7.1	7.0	7.2	7.1	7.0	6.9	6.7
			7.0	7.8	7.7	7.5	7.4	7.7	7.6	7.5	7.4	7.5	7.4	7.3	7.2	7.4	7.3	7.2	7.1	6.9
			10.0	7.9	7.8	7.7	7.6	7.8	7.7	7.6	7.5	7.6	7.5	7.5	7.4	7.4	7.4	7.3	7.3	7.1

