

# 屋内照明器具特性

品番 (品名)	YK34880Z															
光源	K-HICA400F.G ×1 19500.0 lm															
管理番号	K0058228 (* ) DJ 1															
BZ分類	BZ3/0.7/BZ2/4.5/BZ3/6.0/BZ2															

器具効率	45 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 ( X0.01 ) ZCM																		
下方光束	45 %																				
保守率	良 中 否	0.78	0.6	2.9	2.5	2.2	2.0	2.9	2.5	2.2	2.0	2.8	2.4	2.2	2.0	2.7	2.4	2.2	2.0	1.9	
		0.74	0.8	3.4	3.0	2.7	2.5	3.3	3.0	2.7	2.5	3.2	2.9	2.7	2.5	3.1	2.9	2.6	2.5	2.4	
			1.0	3.7	3.3	3.0	2.9	3.6	3.3	3.0	2.8	3.5	3.2	3.0	2.8	3.4	3.2	3.0	2.8	2.7	
		0.65	1.25	3.9	3.6	3.3	3.2	3.8	3.6	3.3	3.1	3.7	3.5	3.3	3.1	3.6	3.4	3.2	3.1	3.0	
下方投影面積	c m <sup>2</sup>	1.5	4.1	3.8	3.5	3.4	4.0	3.7	3.5	3.4	3.9	3.7	3.5	3.3	3.8	3.6	3.4	3.3	3.2		
		2.0	4.3	4.0	3.8	3.7	4.2	4.0	3.8	3.7	4.1	3.9	3.7	3.6	4.0	3.8	3.7	3.6	3.5		
等価発光面積	c m <sup>2</sup>	2.5	4.4	4.2	4.0	3.9	4.3	4.1	4.0	3.8	4.2	4.0	3.9	3.8	4.1	4.0	3.9	3.8	3.7		
		3.0	4.5	4.3	4.1	4.0	4.4	4.2	4.1	4.0	4.3	4.2	4.0	3.9	4.2	4.1	4.0	3.9	3.8		
取付高さ	器具間隔最大限		H m	1.16 H m	H m	1.16 H m	4.0	4.6	4.4	4.3	4.2	4.5	4.4	4.3	4.2	4.4	4.3	4.2	4.1	4.0	3.9
	5.0	4.6					4.5	4.4	4.3	4.6	4.5	4.4	4.3	4.4	4.4	4.3	4.2	4.3	4.3	4.2	4.1
			7.0	4.7	4.6	4.5	4.5	4.6	4.5	4.5	4.4	4.5	4.5	4.4	4.4	4.4	4.3	4.3	4.1		
			10.0	4.7	4.7	4.6	4.6	4.7	4.6	4.6	4.5	4.6	4.5	4.5	4.4	4.5	4.4	4.4	4.2		

