

屋内照明器具特性

品番 (品名)	YYY86010									
光源	YYY86010 ×1					371.0 lm				
管理番号	K0121186(0)DD1									
BZ分類	BZ1									

器具効率	99%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	99%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	73	65	59	56	72	64	59	56	70	63	59	56	69	63	58	55	54
	中	0.67	0.8	81	74	69	65	80	73	68	65	78	72	68	65	76	71	67	64	63
	否	0.63	1.0	86	80	75	71	85	79	75	71	83	78	74	71	81	77	73	70	69
			1.25	91	85	80	77	89	84	80	77	87	83	79	76	85	81	78	76	74
下方投影面積			1.5	93	88	84	81	92	87	83	80	90	86	83	80	88	84	82	79	77
			2.0	97	93	89	86	96	92	88	86	93	90	87	85	91	89	86	84	82
取付高さ	器具間隔最大限		2.5	99	95	92	90	98	94	92	89	95	93	90	88	93	91	89	87	85
	横方向 (A)	縦方向 (B)	3.0	100	97	95	92	99	96	94	92	97	94	92	91	95	93	91	89	87
Hm	0.54Hm	1.18Hm	4.0	102	100	98	96	101	99	97	95	99	97	95	94	97	95	94	92	90
			5.0	103	101	99	98	102	100	99	97	100	98	97	96	98	96	95	94	92
			7.0	104	103	102	100	103	102	101	100	101	100	99	98	99	98	97	96	94
			10.0	105	104	103	103	104	103	102	102	102	101	100	100	100	99	99	98	95

