

屋内照明器具特性

品番 (品名)	NNN13600S															
光源	LDA14L - G / K100 / W ×1 1520.0 lm															
管理番号	K0138605 (0) DB 1															
BZ分類	BZ4 / 0.7 / BZ3															

器具効率	35 %	天井	80 %				70 %				50 %				30 %				0 %		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
		床	10 %				10 %				10 %				10 %				0 %		
上方光束	0 %																				
下方光束	35 %																				
室指数	照明率 (X0.01) ZCM																				
保守率	良 0.63 中 0.6 否 0.56	0.6	21	17	15	13	21	17	15	13	20	17	15	13	19	16	14	13	12		
		0.8	25	21	19	17	24	21	19	17	24	21	18	17	23	20	18	17	16		
		1.0	27	24	22	20	27	24	21	20	26	23	21	20	25	23	21	20	19		
		1.25	29	26	24	23	29	26	24	22	28	26	24	22	27	25	23	22	21		
下方投影面積	cm ²	1.5	31	28	26	24	30	28	26	24	29	27	25	24	28	27	25	24	23		
		2.0	32	30	29	27	32	30	28	27	31	29	28	27	30	29	27	26	26		
取付高さ	器具間隔最大限		2.5	34	32	30	29	33	31	30	29	32	31	29	28	31	30	29	28		
	横方向 (A)	縦方向 (B)	3.0	34	33	31	30	34	32	31	30	33	32	31	30	32	31	30	29	28	
Hm	1.34 Hm	1.18 Hm	4.0	35	34	33	32	35	34	33	32	34	33	32	31	33	32	31	31	30	
			5.0	36	35	34	33	35	34	34	33	34	34	33	32	34	33	32	32	31	
			7.0	36	36	35	34	36	35	35	34	35	34	34	33	34	34	33	33	33	32
			10.0	37	36	36	35	36	36	35	35	35	35	35	35	34	35	34	34	34	33

