




- 断熱材施工
不可
- 
- A square prohibition sign with a thick black border. Inside, the text "断熱材施工" (Thermal insulation construction) is at the top, and "不可" (Prohibited) is below it. At the bottom, there is a graphic of a thermal insulation material roll with a large 'X' over it, indicating that such construction is not allowed.



＜使用上のご注意＞


-
- Technical drawing of a circular terminal block. The drawing shows a circular component with a diameter of 480. The center is marked with a crosshair. There are four mounting holes, each with a diameter of 26 (Ø26穴), arranged in a square pattern. The distance between the centers of the holes is 125. The distance from the center of the component to the center of the holes is 50. The component has a capacity of 20A (容量20A) and includes a terminal block (端子台) for power supply (電源用). The terminal block is labeled as 2-Ø20穴 (取付ボルト用) and is used for power supply (電源用). The component is also labeled as 7.

＜施工上のご注意＞

-
- ボルト引き込みしろ
天井面から85~110mm
取付ボルト
- 1
2
3
4
5
6
- Ø595
Ø620
125
8
344
270

	定格電圧	AC100V	AC200V	AC242V	器具光束・消費電力・消費効率
LT9	入力電流	0.69A	0.34A	0.29A	7180lm・67W・107.1lm/W
	消費電力	69W	67W	67W	

杵部詳細図

埋込穴寸法： $\varnothing 600$

埋込穴寸法：φ600		7	電源ユニット		1 台	品 番 NNF82601C
		6	LEDユニット		64粒×2	
ホワイト マンセル 1.0G9.6/0.1		5	LEDユニット		56粒×2	
LED	白色 (4000K、Ra83)	4	パネル	アクリル (t1.5)	乳 白	福 田
器具質量	7.6kg	3	枠	銅板 (t0.8)	高反射白色粉体塗装	
特記事項		2	反 射 板	銅板 (t0.8)	高反射白色粉体塗装	
		1	本 体	銅板 (t0.8)	高反射白色粉体塗装	
		部 番	部 品 名	材質・素材厚	備 考	パナソニック株式会社