

# 屋内照明器具特性

品番 (品名)	LGB10937									
光源	LED2700_70_138 x1					138.0 lm				
管理番号	K0138378(0)DB1									
BZ分類	BZ4/1.8/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		10%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	90%	床	10%				10%				10%				10%				0%		
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.67	0.6	60	49	41	37	58	48	41	36	55	46	40	36	52	44	39	35	33	
	中	0.63	0.8	68	58	50	45	66	56	50	45	63	54	48	44	59	52	47	43	40	
	否	0.56	1.0	74	64	57	51	72	62	56	51	68	60	54	50	64	57	52	48	45	
			1.25	79	70	63	58	77	68	62	57	72	65	60	55	69	63	58	54	51	
下方投影面積			cm <sup>2</sup>	1.5	83	74	68	62	80	72	66	61	76	69	64	60	72	66	62	58	54
等価発光面積			cm <sup>2</sup>	2.0	88	80	74	70	85	78	73	68	81	75	70	66	76	72	68	65	60
取付高さ	器具間隔最大限		H <sub>m</sub>	2.5	91	84	79	75	88	82	78	73	84	79	75	71	79	75	72	69	65
	横方向 (A)	縦方向 (B)		3.0	93	87	83	78	90	85	81	77	86	82	78	75	82	78	75	72	68
	0.89H <sub>m</sub>	0.89H <sub>m</sub>	4.0	96	91	87	84	93	89	86	82	89	85	82	79	84	82	79	77	72	
			5.0	98	94	90	87	95	92	89	86	91	88	85	83	86	84	82	80	75	
			7.0	100	97	94	92	97	95	92	90	93	91	89	87	89	87	85	83	78	
			10.0	101	99	97	95	99	97	95	93	95	93	91	90	90	89	88	86	81	

