

屋内照明器具特性

品番 (品名)	LGB51523									
光源	LED2700_70_410 x1					410.0 lm				
管理番号	K0141819(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
		床	10%				10%				10%				10%				0%		
上方光束	4%																				
下方光束	96%																				
室指数	照明率 (X0.01)																		ZCM		
保守率	良 中 否	0.63	0.6	0.6	56	44	36	31	55	43	36	31	52	42	35	30	49	41	34	30	28
		0.6	0.6	0.6	66	55	47	41	64	54	46	41	61	52	45	40	58	50	44	40	37
		0.56	0.6	0.6	73	62	54	49	71	61	54	48	67	59	53	48	64	57	51	47	44
		0.56	0.6	0.6	79	69	62	56	77	68	61	56	73	66	60	55	70	63	58	54	51
下方投影面積	c m ²	1.5	83	74	67	62	81	73	66	61	77	70	65	60	74	68	63	59	56		
		2.0	88	81	75	70	86	80	74	69	83	77	72	68	79	74	70	67	63		
取付高さ	器具間隔最大限		2.5	92	86	80	76	90	84	79	75	86	81	77	73	83	79	75	72	68	
	横方向 (A)	縦方向 (B)	3.0	94	89	84	80	92	87	83	79	89	84	81	77	85	82	78	76	72	
H m	1.26 H m	1.26 H m	4.0	97	93	89	86	96	91	88	85	92	89	85	83	89	86	83	81	77	
			5.0	99	96	92	89	97	94	91	88	94	91	88	86	91	88	86	84	80	
			7.0	102	99	96	94	100	97	95	93	96	94	92	90	93	91	90	88	84	
			10.0	103	101	99	97	101	100	98	96	98	97	95	94	95	94	92	91	87	

