

屋内照明器具特性

品番 (品名)	FYY22230				
光源	LED3000_85_2340 x1 2340.0 1m				
管理番号	K0166073(0)DB1				
BZ分類	BZ5/3.5/BZ6/4.5/BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%					
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
下方光束	100%	床		10%				10%				10%				10%				0%				
室指数	照明率 (X0.01)																			ZCM				
保守率	良	0.83	0.6	5.5	4.2	3.4	2.8	5.3	4.1	3.4	2.8	5.1	4.0	3.3	2.8	4.9	3.9	3.3	2.8	2.6				
	中	0.81	0.8	6.4	5.2	4.4	3.8	6.3	5.1	4.3	3.7	6.0	5.0	4.3	3.7	5.7	4.8	4.2	3.7	3.5				
	否	0.77	1.0	7.1	5.9	5.1	4.4	6.9	5.8	5.0	4.4	6.6	5.6	4.9	4.4	6.3	5.5	4.9	4.4	4.1				
			1.25	7.6	6.6	5.8	5.1	7.5	6.5	5.7	5.1	7.1	6.3	5.6	5.1	6.8	6.1	5.5	5.0	4.8				
下方投影面積	c m ²		1.5	8.1	7.1	6.3	5.7	7.9	7.0	6.2	5.6	7.5	6.7	6.1	5.6	7.2	6.6	6.0	5.5	5.3				
等価発光面積	c m ²		2.0	8.6	7.8	7.1	6.5	8.4	7.7	7.0	6.5	8.1	7.4	6.9	6.4	7.8	7.2	6.7	6.3	6.0				
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.6	7.1	8.8	8.1	7.5	7.0	8.5	7.9	7.5	8.8	8.2	7.8	7.4	8.5	8.0	7.6	7.3	7.0	
	横方向 (A)	縦方向 (B)																						
1.5m	1.93m	1.8m	4.0	9.6	9.1	8.6	8.2	9.4	8.9	8.5	8.1	9.1	8.7	8.3	8.0	8.8	8.5	8.2	7.9	7.6				
2	2.49	2.42	5.0	9.8	9.4	9.0	8.6	9.7	9.3	8.9	8.5	9.4	9.0	8.7	8.4	9.1	8.8	8.5	8.2	8.0				
2.5	3.05	3.01	7.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.1	9.6	9.4	9.1	8.9	9.4	9.2	8.9	8.7	8.4				
3	3.62	3.68	10.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.1	8.8				

