

# 屋内照明器具特性

品番 (品名)	LGB52096				
光源	LED5000_70_980	x1	980.0 lm		
管理番号	K0139435(1)DR1				
BZ分類	BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		11%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		89%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	54	42	34	29	52	41	33	28	49	39	32	28	46	37	31	27	24	
	中	0.6	0.8	64	52	44	38	62	51	43	38	58	49	42	37	54	46	40	36	33	
	否	0.56	1.0	70	59	52	46	68	58	51	45	64	55	49	44	60	52	47	42	39	
			1.25	76	66	59	53	74	65	58	52	69	61	55	51	65	58	53	49	45	
下方投影面積			cm <sup>2</sup>	1.5	80	71	64	58	78	69	63	57	73	66	60	56	69	63	58	54	50
	等価発光面積		cm <sup>2</sup>	2.0	86	78	72	67	83	76	70	66	79	73	68	63	74	69	65	61	57
取付高さ	器具間隔最大限			2.5	90	83	77	72	87	81	76	71	82	77	73	69	77	73	70	66	62
	横方向 (A)	縦方向 (B)		3.0	92	86	81	77	89	84	79	75	85	80	76	73	80	76	73	70	65
1.5m	2.01m	1.89m		4.0	95	91	86	83	93	88	85	81	88	84	81	78	83	80	78	75	70
2	2.67	2.49		5.0	97	93	90	86	95	91	88	85	90	87	84	82	85	83	80	78	73
2.5	3.34	3.09		7.0	100	97	94	91	97	94	92	89	92	90	88	86	88	86	84	82	77
3	3.97	3.67		10.0	101	99	97	95	99	97	95	93	94	92	91	89	90	88	87	86	80

