

屋内照明器具特性	
品番 (品名)	LGB52095
光源	LED5000_70_980 ×1 980.0 lm
管理番号	K0139435 (1) DR1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%									
	上方光束		11%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%							
	下方光束		89%		床	10%				10%				10%				10%				0%						
室指数	照明率 (X0.01)																			ZCM								
保守率	良	0.63	0.6	0.6	54	42	34	29	52	41	33	28	49	39	32	28	46	37	31	27	24							
	中	0.6	0.6	0.6	64	52	44	38	62	51	43	38	58	49	42	37	54	46	40	36	33							
	否	0.56	0.56	0.56	70	59	52	46	68	58	51	45	64	55	49	44	60	52	47	42	39							
	0.56	0.56	0.56	76	66	59	53	74	65	58	52	69	61	55	51	65	58	53	49	45								
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0																	
	等価発光面積		c m ²																									
取付高さ	器具間隔最大限																											
	横方向 (A)	縦方向 (B)																										
1.5m	2.01m	1.89m	4.0	95	91	86	83	93	88	85	81	88	84	81	78	83	80	78	75	70								
2	2.67	2.49	5.0	97	93	90	86	95	91	88	85	90	87	84	82	85	83	80	78	73								
2.5	3.34	3.09	7.0	100	97	94	91	97	94	92	89	92	90	88	86	88	86	84	82	77								
3	3.97	3.67	10.0	101	99	97	95	99	97	95	93	94	92	91	89	90	88	87	86	80								

