

| | |
|----------|----------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | LGW80168 |
| 光源 | LED5000_70_855 x1 855.0 lm |
| 管理番号 | K0130891(0)DB1 |
| BZ分類 | BZ6 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------------------------|----------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 16% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 84% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 0.63 中 0.6 否 0.56 | 0.6 | 51 | 39 | 30 | 25 | 49 | 37 | 30 | 24 | 45 | 35 | 28 | 23 | 41 | 33 | 27 | 22 | 19 | |
| | | 0.8 | 60 | 48 | 40 | 34 | 58 | 47 | 39 | 33 | 53 | 44 | 37 | 32 | 49 | 41 | 35 | 30 | 26 | |
| | | 1.0 | 67 | 55 | 47 | 40 | 64 | 53 | 45 | 39 | 59 | 50 | 43 | 38 | 54 | 46 | 41 | 36 | 32 | |
| | | 1.25 | 72 | 62 | 53 | 47 | 69 | 60 | 52 | 46 | 64 | 56 | 49 | 44 | 59 | 52 | 46 | 42 | 37 | |
| 下方投影面積 | c m ² | 1.5 | 77 | 66 | 59 | 52 | 73 | 64 | 57 | 51 | 68 | 60 | 54 | 49 | 62 | 56 | 51 | 46 | 42 | |
| | | 2.0 | 82 | 74 | 66 | 61 | 79 | 71 | 65 | 59 | 73 | 67 | 61 | 56 | 68 | 62 | 57 | 53 | 48 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 86 | 78 | 72 | 66 | 83 | 76 | 70 | 65 | 77 | 71 | 66 | 61 | 71 | 66 | 62 | 58 | 53 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 89 | 82 | 76 | 71 | 85 | 79 | 74 | 69 | 79 | 74 | 70 | 66 | 74 | 69 | 66 | 62 | 56 |
| H m | 1.34 H m | 1.31 H m | 4.0 | 92 | 86 | 81 | 77 | 89 | 84 | 79 | 75 | 83 | 78 | 75 | 71 | 77 | 74 | 70 | 67 | 61 |
| | | | 5.0 | 94 | 89 | 85 | 81 | 91 | 87 | 83 | 79 | 85 | 81 | 78 | 75 | 79 | 76 | 74 | 71 | 64 |
| | | | 7.0 | 97 | 93 | 90 | 86 | 94 | 90 | 87 | 84 | 88 | 85 | 82 | 80 | 82 | 80 | 78 | 75 | 69 |
| | | | 10.0 | 99 | 96 | 93 | 91 | 96 | 93 | 91 | 88 | 90 | 88 | 86 | 84 | 84 | 83 | 81 | 79 | 72 |

