

屋内照明器具特性

品番 (品名)	L G W 8 0 1 9 0	
光源	L G W 8 0 1 9 0 (H 1) × 1	1 0 6 2 . 0 l m
管理番号	K 0 1 2 7 9 7 0 (0) D B 1	
B Z 分類	B Z 6	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	19 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	81 %	室指数	照明率 (X 0 . 0 1)																Z C M	
保守率	良 中 否	0.63	0.6	50	38	30	24	48	36	29	23	44	34	27	22	40	31	25	21	18
		0.6	0.8	60	47	39	33	57	46	38	32	52	42	36	30	47	39	33	29	25
			1.0	66	54	46	40	63	52	45	39	58	49	42	37	52	45	39	35	30
		0.56	1.25	72	61	53	47	69	59	51	45	63	55	48	43	57	51	45	41	36
下方投影面積	c m ²	1.5	76	66	58	52	73	64	56	51	67	59	53	48	61	55	50	45	40	
		2.0	82	73	66	60	78	71	64	59	72	66	60	55	66	61	56	52	46	
取付高さ	器具間隔最大限		2.5	86	78	72	66	82	75	69	64	76	70	65	61	70	65	61	57	51
	横方向 (A)	縦方向 (B)	3.0	88	81	76	71	85	79	73	69	78	73	69	65	72	68	64	61	54
1.5m	2.3 m	1.96 m	4.0	92	86	81	77	88	83	79	75	82	77	74	70	75	72	69	66	59
2	3.06	2.58	5.0	94	89	85	81	90	86	82	79	84	80	77	74	78	75	72	70	62
2.5	3.84	3.21	7.0	96	93	89	86	93	90	87	84	87	84	81	79	80	78	76	74	67
3	4.6	3.84	10.0	98	96	93	91	95	93	90	88	89	87	85	83	83	81	79	78	70

