

屋内照明器具特性	
品番 (品名)	L S E B 3 2 0 7
光源	LED2700_70_216 ×1 216.0 l m
管理番号	K0130313 (0) DB 1
B Z 分類	BZ5 / 0.7 / BZ4 / 6.0 / BZ5

器具効率		100 % 上方光束 12 % 下方光束 88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	57	45	37	32	55	44	37	32	51	42	36	31	48	40	34	30	28
			0.63	0.8	67	56	49	43	65	55	48	43	61	52	46	42	57	50	45	41	37
			0.56	1.0	74	64	57	51	71	62	56	51	67	59	54	49	63	57	52	48	44
				1.25	79	70	64	59	77	69	63	58	72	65	60	56	68	62	58	54	50
下方投影面積 等価発光面積		cm ² cm ²		1.5	83	75	69	64	81	73	67	63	76	70	65	61	72	66	62	59	55
			2.0	88	82	76	71	86	80	74	70	81	76	71	68	76	72	68	65	61	
取付 高さ	器具間隔最大限		2.5	91	86	81	77	89	84	79	75	84	79	76	72	79	76	73	70	65	
	横方向 (A) 縦方向 (B)		3.0	94	88	84	80	91	86	82	79	86	82	79	76	81	78	75	73	68	
H m	1.39 H m 1.39 H m		4.0	96	92	89	85	94	90	87	84	89	86	83	80	84	82	79	77	72	
			5.0	98	95	92	89	95	92	89	87	90	88	86	83	86	84	82	80	74	
			7.0	100	97	95	93	97	95	93	91	92	90	89	87	88	86	85	83	77	
			10.0	102	100	98	96	99	97	96	94	94	93	91	90	89	88	87	86	80	

