

屋内照明器具特性

品番 (品名)	L G W 8 0 2 4 6															
光源	LED2700_70_95 x1 95.0 l m															
管理番号	K0136362 (0) DB 1															
B Z 分類	BZ7 / 0.7 / BZ6															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	5 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	95 %		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.63	0.6	50	37	28	22	49	36	28	22	45	34	27	22	43	33	26	21	19
		0.6	0.8	60	47	38	31	58	46	37	31	54	44	36	30	51	42	35	30	27
			1.0	66	54	45	38	64	52	44	37	60	50	43	37	56	48	41	36	33
		0.56	1.25	72	60	52	45	70	59	51	44	66	56	49	44	62	54	48	43	39
下方投影面積	c m ²	1.5	76	66	57	51	74	64	56	50	70	61	54	49	66	59	53	48	44	
		2.0	83	73	66	59	80	72	64	58	76	68	62	57	72	66	60	56	52	
取付高さ	器具間隔最大限		2.5	86	78	71	65	84	77	70	65	80	73	68	63	76	70	66	61	58
	横方向 (A)	縦方向 (B)	3.0	89	82	76	70	87	80	74	69	83	77	72	67	79	74	70	66	62
H m	1.46 H m	1.46 H m	4.0	93	87	82	77	91	85	80	76	87	82	78	74	83	79	75	72	68
			5.0	95	90	86	81	93	89	84	80	89	85	81	78	85	82	79	76	72
			7.0	98	94	91	87	96	93	89	86	92	89	86	83	88	86	83	81	77
			10.0	101	98	95	92	99	96	93	91	95	92	90	88	91	89	87	85	81

