

屋内照明器具特性

品番 (品名)	L G W C 8 0 2 3 0	
光源	LED2700_70_263 x1	263.0 l m
管理番号	K0135302 (0) DB 1	
B Z 分類	B Z 7 / 0 . 7 / B Z 6 / 2 . 3 / B Z 5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	6 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	94 %		室指数	照明率 (X 0 . 0 1)																Z C M
保守率	良	0.63	0.6	4.9	3.5	2.6	2.0	4.7	3.4	2.6	2.0	4.4	3.3	2.5	1.9	4.1	3.1	2.4	1.9	1.6
	中	0.6	0.8	5.9	4.6	3.7	3.1	5.7	4.5	3.7	3.0	5.4	4.3	3.5	3.0	5.0	4.1	3.4	2.9	2.6
	否	0.56	1.0	6.7	5.4	4.6	3.9	6.5	5.3	4.5	3.9	6.1	5.1	4.3	3.8	5.7	4.8	4.2	3.7	3.4
			1.25	7.3	6.2	5.4	4.7	7.1	6.1	5.3	4.7	6.7	5.8	5.1	4.6	6.3	5.6	4.9	4.5	4.1
下方投影面積	c m ²		1.5	7.8	6.8	6.0	5.4	7.6	6.7	5.9	5.3	7.2	6.4	5.7	5.2	6.8	6.1	5.5	5.1	4.7
等価発光面積	c m ²		2.0	8.5	7.6	6.9	6.3	8.3	7.5	6.8	6.3	7.8	7.2	6.6	6.1	7.4	6.9	6.4	6.0	5.6
取付高さ	器具間隔最大限		2.5	8.9	8.2	7.5	7.0	8.7	8.0	7.4	6.9	8.2	7.7	7.2	6.7	7.8	7.3	6.9	6.6	6.2
	横方向 (A)	縦方向 (B)	3.0	9.2	8.5	8.0	7.5	8.9	8.3	7.8	7.4	8.5	8.0	7.6	7.2	8.1	7.7	7.3	7.0	6.6
H m	0.00 H m	0.00 H m	4.0	9.5	9.0	8.5	8.1	9.3	8.8	8.4	8.0	8.9	8.5	8.1	7.8	8.5	8.2	7.9	7.6	7.2
			5.0	9.7	9.3	8.9	8.6	9.5	9.1	8.8	8.4	9.1	8.8	8.5	8.2	8.7	8.4	8.2	7.9	7.5
			7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	8.9	9.4	9.1	8.9	8.7	9.0	8.8	8.6	8.4	8.0
			10.0	10.2	9.9	9.7	9.5	10.0	9.8	9.6	9.4	9.6	9.4	9.2	9.1	9.2	9.1	8.9	8.8	8.3

