

|          |                             |
|----------|-----------------------------|
| 屋内照明器具特性 |                             |
| 品番 (品名)  | LSEB2039                    |
| 光源       | LED2700_70_410 x1 410.0 l m |
| 管理番号     | K0141819 (0) DB 1           |
| BZ分類     | BZ5                         |

|                |                    |                    |               |      |      |     |      |      |      |     |      |     |     |     |      |     |     |     |     |     |
|----------------|--------------------|--------------------|---------------|------|------|-----|------|------|------|-----|------|-----|-----|-----|------|-----|-----|-----|-----|-----|
| 器具効率           | 100 %              | 天井                 | 80 %          |      |      |     | 70 % |      |      |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |     |
|                |                    | 壁                  | 70            | 50   | 30   | 10  | 70   | 50   | 30   | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |     |
| 上方光束           | 4 %                | 床                  | 10 %          |      |      |     | 10 % |      |      |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |     |
| 下方光束           | 96 %               | 室指数                | 照明率 ( X0.01 ) |      |      |     |      |      |      |     |      |     |     |     |      |     |     |     | ZCM |     |
| 保守率            | 良                  | 0.63               | 0.6           | 5.6  | 4.4  | 3.6 | 3.1  | 5.5  | 4.3  | 3.6 | 3.1  | 5.2 | 4.2 | 3.5 | 3.0  | 4.9 | 4.1 | 3.4 | 3.0 | 2.8 |
|                | 中                  | 0.6                | 0.8           | 6.6  | 5.5  | 4.7 | 4.1  | 6.4  | 5.4  | 4.6 | 4.1  | 6.1 | 5.2 | 4.5 | 4.0  | 5.8 | 5.0 | 4.4 | 4.0 | 3.7 |
|                | 否                  | 0.56               | 1.0           | 7.3  | 6.2  | 5.4 | 4.9  | 7.1  | 6.1  | 5.4 | 4.8  | 6.7 | 5.9 | 5.3 | 4.8  | 6.4 | 5.7 | 5.1 | 4.7 | 4.4 |
|                |                    |                    | 1.25          | 7.9  | 6.9  | 6.2 | 5.6  | 7.7  | 6.8  | 6.1 | 5.6  | 7.3 | 6.6 | 6.0 | 5.5  | 7.0 | 6.3 | 5.8 | 5.4 | 5.1 |
| 下方投影面積         |                    | cm <sup>2</sup>    | 1.5           | 8.3  | 7.4  | 6.7 | 6.2  | 8.1  | 7.3  | 6.6 | 6.1  | 7.7 | 7.0 | 6.5 | 6.0  | 7.4 | 6.8 | 6.3 | 5.9 | 5.6 |
| 等価発光面積         |                    | cm <sup>2</sup>    | 2.0           | 8.8  | 8.1  | 7.5 | 7.0  | 8.6  | 8.0  | 7.4 | 6.9  | 8.3 | 7.7 | 7.2 | 6.8  | 7.9 | 7.4 | 7.0 | 6.7 | 6.3 |
| 取付高さ           | 器具間隔最大限            |                    | 2.5           | 9.2  | 8.6  | 8.0 | 7.6  | 9.0  | 8.4  | 7.9 | 7.5  | 8.6 | 8.1 | 7.7 | 7.3  | 8.3 | 7.9 | 7.5 | 7.2 | 6.8 |
|                | 横方向 (A)            | 縦方向 (B)            | 3.0           | 9.4  | 8.9  | 8.4 | 8.0  | 9.2  | 8.7  | 8.3 | 7.9  | 8.9 | 8.4 | 8.1 | 7.7  | 8.5 | 8.2 | 7.8 | 7.6 | 7.2 |
| H <sub>m</sub> | 1.26H <sub>m</sub> | 1.26H <sub>m</sub> | 4.0           | 9.7  | 9.3  | 8.9 | 8.6  | 9.6  | 9.1  | 8.8 | 8.5  | 9.2 | 8.9 | 8.5 | 8.3  | 8.9 | 8.6 | 8.3 | 8.1 | 7.7 |
|                |                    |                    | 5.0           | 9.9  | 9.6  | 9.2 | 8.9  | 9.7  | 9.4  | 9.1 | 8.8  | 9.4 | 9.1 | 8.8 | 8.6  | 9.1 | 8.8 | 8.6 | 8.4 | 8.0 |
|                |                    |                    | 7.0           | 10.2 | 9.9  | 9.6 | 9.4  | 10.0 | 9.7  | 9.5 | 9.3  | 9.6 | 9.4 | 9.2 | 9.0  | 9.3 | 9.1 | 9.0 | 8.8 | 8.4 |
|                |                    |                    | 10.0          | 10.3 | 10.1 | 9.9 | 9.7  | 10.1 | 10.0 | 9.8 | 9.6  | 9.8 | 9.7 | 9.5 | 9.4  | 9.5 | 9.4 | 9.2 | 9.1 | 8.7 |

