

屋内照明器具特性

品番 (品名)	LSEB7201									
光源	LED2700_70_850 x1					850.0 lm				
管理番号	K0138505 (1) DB1									
BZ分類	BZ6/0.7/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		17%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		83%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	
	等価発光面積		c m ²																		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
1.5m	2.12m	1.88m	4.0	9.3	8.8	8.4	8.0	9.0	8.5	8.1	7.7	8.4	8.0	7.7	7.3	7.8	7.5	7.2	6.9	6.3	
2	2.82	2.48	5.0	9.5	9.1	8.7	8.3	9.2	8.8	8.5	8.1	8.6	8.3	8.0	7.7	8.0	7.7	7.5	7.3	6.6	
2.5	3.54	3.08	7.0	9.8	9.4	9.1	8.8	9.4	9.1	8.9	8.6	8.8	8.6	8.4	8.1	8.3	8.1	7.9	7.7	7.0	
3	4.2	3.66	10.0	9.9	9.7	9.5	9.3	9.6	9.4	9.2	9.0	9.0	8.8	8.7	8.5	8.5	8.3	8.2	8.0	7.3	

