

屋内照明器具特性	
品番 (品名)	LSEB7202
光源	LED5000_70_840 x1 840.0 l m
管理番号	K0140471(0)DB1
BZ分類	BZ6/0.7/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	17%	床	10%				10%				10%				10%				0%	
下方光束	83%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	5.2	4.0	3.2	2.6	5.0	3.8	3.1	2.6	4.6	3.6	2.9	2.5	4.2	3.4	2.8	2.4	2.1	
		0.8	6.2	5.0	4.2	3.6	5.9	4.8	4.0	3.5	5.4	4.5	3.8	3.3	5.0	4.2	3.6	3.2	2.8	
		1.0	6.8	5.7	4.9	4.3	6.5	5.5	4.7	4.2	6.0	5.1	4.5	4.0	5.5	4.8	4.2	3.8	3.4	
		1.25	7.4	6.3	5.6	5.0	7.1	6.1	5.4	4.9	6.5	5.7	5.1	4.6	6.0	5.4	4.8	4.4	3.9	
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	7.8	6.8	6.1	5.5	7.5	6.6	5.9	5.4	6.9	6.2	5.6	5.1	6.4	5.8	5.3	4.9	4.4	
		2.0	8.4	7.5	6.9	6.3	8.0	7.3	6.7	6.2	7.4	6.8	6.3	5.9	6.9	6.4	5.9	5.6	5.0	
		2.5	8.7	8.0	7.4	6.9	8.4	7.7	7.2	6.7	7.8	7.2	6.8	6.4	7.2	6.8	6.4	6.1	5.5	
		3.0	9.0	8.3	7.8	7.3	8.6	8.1	7.6	7.2	8.0	7.6	7.1	6.8	7.4	7.1	6.7	6.4	5.8	
取付高さ	器具間隔最大限		4.0	9.3	8.8	8.3	7.9	9.0	8.5	8.1	7.7	8.4	8.0	7.6	7.3	7.8	7.5	7.2	6.9	6.3
	横方向 (A)	縦方向 (B)																		
1.5m	2.12 m	1.86 m	5.0	9.5	9.1	8.7	8.3	9.2	8.8	8.4	8.1	8.6	8.2	8.0	7.7	8.0	7.7	7.5	7.3	6.6
2	2.84	2.47	7.0	9.7	9.4	9.1	8.8	9.4	9.1	8.9	8.6	8.8	8.6	8.3	8.1	8.2	8.0	7.8	7.7	7.0
2.5	3.53	3.08	10.0	9.9	9.7	9.5	9.2	9.6	9.4	9.2	9.0	9.0	8.8	8.7	8.5	8.4	8.3	8.1	8.0	7.3
3	4.24	3.69																		

