

屋内照明器具特性

品番 (品名)	L S E W4 0 1 6				
光源	LED2700_70_815 x1		815.0 l m		
管理番号	K0130891 (0) DB 1				
B Z 分類	B Z 6				

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		16 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		84 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			Z C M	
保守率	良	0.63	0.6	51	39	30	25	49	37	30	24	45	35	28	23	41	33	27	22	19	
	中	0.6	0.8	60	48	40	34	58	47	39	33	53	44	37	32	49	41	35	30	26	
	否	0.56	1.0	67	55	47	40	64	53	45	39	59	50	43	38	54	46	41	36	32	
	下方投影面積	c m ²		1.25	72	62	53	47	69	60	52	46	64	56	49	44	59	52	46	42	37
等価発光面積	c m ²		1.5	77	66	59	52	73	64	57	51	68	60	54	49	62	56	51	46	42	
	c m ²		2.0	82	74	66	61	79	71	65	59	73	67	61	56	68	62	57	53	48	
取付高さ	器具間隔最大限		2.5	86	78	72	66	83	76	70	65	77	71	66	61	71	66	62	58	53	
	横方向 (A)	縦方向 (B)	3.0	89	82	76	71	85	79	74	69	79	74	70	66	74	69	66	62	56	
H m	1.34 H m	1.31 H m	4.0	92	86	81	77	89	84	79	75	83	78	75	71	77	74	70	67	61	
			5.0	94	89	85	81	91	87	83	79	85	81	78	75	79	76	74	71	64	
			7.0	97	93	90	86	94	90	87	84	88	85	82	80	82	80	78	75	69	
			10.0	99	96	93	91	96	93	91	88	90	88	86	84	84	83	81	79	72	

