

屋内照明器具特性

品番 (品名)	NNF 4 1 8 7 5																	
光源	LED_READING5000_85_1780 ×1 1780.0 1m																	
管理番号	K0135882(0)DB1																	
BZ分類	BZ4/0.7/BZ3																	

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	1%	室指数	照明率 (X0.01)																		ZCM
下方光束	99%																				
保守率	良 中 否	0.83	0.6	61	50	43	38	60	50	43	38	58	49	43	38	56	48	42	38	36	
		0.81	0.8	72	62	55	50	71	61	54	50	68	60	54	49	66	58	53	49	47	
		0.77	1.0	79	69	63	58	77	68	62	57	74	67	61	57	72	66	61	57	55	
			1.25	84	76	70	65	83	75	69	65	80	73	68	64	77	72	67	64	62	
下方投影面積	c m ²	1.5	88	81	75	70	86	80	74	70	84	78	73	69	81	76	72	69	66		
		2.0	93	87	82	78	91	86	81	77	89	84	80	76	86	82	78	76	73		
取付高さ	器具間隔最大限		2.5	96	91	86	83	94	90	86	82	92	88	84	81	89	86	83	80	78	
	横方向 (A)	縦方向 (B)	3.0	98	93	90	86	96	92	89	86	94	90	87	84	91	88	86	83	81	
1.5m	1.24m	2.04m	4.0	100	97	94	91	99	96	93	90	96	94	91	89	94	91	89	88	85	
2	1.66	2.63	5.0	102	99	96	94	101	98	95	93	98	96	94	92	95	94	92	90	87	
2.5	2.07	3.24	7.0	104	102	100	98	102	100	99	97	100	98	97	95	97	96	95	93	90	
3	2.48	3.86	10.0	105	103	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93	

