

屋内照明器具特性	
品番 (品名)	NNN53820B
光源	LDA7L-G/D/S/K6 ×1 810.0 lm
管理番号	K0169147 (0) DR 1
BZ分類	BZ4

器具効率		45 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																			
下方光束		45 %		Z CM																			
保守率		良 中 否	0.63	0.6	26	21	18	16	26	21	18	16	25	21	18	16	24	20	17	16	15		
			0.6	0.8	31	26	23	21	31	26	23	21	29	25	23	21	28	25	22	21	20		
			0.56	1.0	34	30	27	24	34	29	27	24	32	29	26	24	31	28	26	24	23		
				1.25	37	33	30	28	36	33	30	28	35	32	29	28	34	31	29	27	26		
下方投影面積		cm ²	1.5	39	35	32	30	38	35	32	30	37	34	32	30	35	33	31	30	29			
等価発光面積			cm ²	2.0	41	38	36	34	40	38	35	34	39	37	35	33	38	36	34	33	32		
取付高さ	器具間隔最大限			2.5	42	40	38	36	42	39	38	36	40	39	37	35	39	38	36	35	34		
H m		1.29 H m		縦方向 (B)		3.0	43	41	39	38	43	41	39	38	41	40	38	37	40	39	38	37	36
H m		1.29 H m		4.0	44	43	41	40	44	42	41	40	43	41	40	39	42	40	40	39	37		
				5.0	45	44	43	42	45	43	42	41	43	42	41	41	42	41	41	40	39		
				7.0	46	45	44	43	45	45	44	43	44	44	43	42	43	43	42	41	40		
				10.0	47	46	45	45	46	45	45	44	45	44	44	43	44	43	43	43	41		

