

屋内照明器具特性	
品番 (品名)	NNN12200W
光源	LDA8L-D-G-E17/S/Z6 ×1 760.0 l m
管理番号	K0172968(0)DR1
BZ分類	BZ8/1.4/BZ7

器具効率	85%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	43%	床	10%				10%				10%				10%				0%	
下方光束	42%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 0.63	0.6	3.8	2.8	2.1	1.7	3.5	2.6	2.0	1.5	2.9	2.1	1.7	1.3	2.3	1.7	1.4	1.1	6	
	中 0.6	0.8	4.6	3.5	2.8	2.3	4.2	3.3	2.6	2.2	3.4	2.7	2.2	1.8	2.8	2.2	1.8	1.5	9	
	否 0.56	1.0	5.1	4.1	3.4	2.8	4.6	3.8	3.1	2.6	3.8	3.1	2.6	2.2	3.1	2.6	2.2	1.9	12	
		1.25	5.5	4.6	3.9	3.4	5.1	4.3	3.6	3.2	4.2	3.6	3.1	2.7	3.4	2.9	2.5	2.2	14	
下方投影面積	cm <sup>2</sup>	1.5	5.9	5.0	4.4	3.8	5.4	4.6	4.0	3.6	4.5	3.9	3.4	3.0	3.6	3.2	2.8	2.5	17	
等価発光面積	cm <sup>2</sup>	2.0	6.3	5.6	5.0	4.5	5.8	5.2	4.6	4.2	4.9	4.4	3.9	3.6	4.0	3.6	3.2	3.0	20	
取付高さ	器具間隔最大限		2.5	6.6	6.0	5.4	5.0	6.1	5.5	5.1	4.6	5.1	4.7	4.3	4.0	4.2	3.8	3.6	3.3	2.2
	横方向 (A)	縦方向 (B)	3.0	6.9	6.3	5.8	5.3	6.3	5.8	5.4	5.0	5.3	4.9	4.6	4.3	4.4	4.1	3.8	3.5	2.4
H <sub>m</sub>	1.58H <sub>m</sub>	1.83H <sub>m</sub>	4.0	7.2	6.7	6.2	5.9	6.6	6.2	5.8	5.5	5.6	5.2	4.9	4.7	4.6	4.3	4.1	3.9	2.7
			5.0	7.3	6.9	6.6	6.2	6.8	6.4	6.1	5.8	5.7	5.5	5.2	5.0	4.8	4.5	4.3	4.1	2.9
			7.0	7.6	7.2	6.9	6.7	7.0	6.7	6.5	6.2	5.9	5.7	5.5	5.3	4.9	4.8	4.6	4.5	3.2
			10.0	7.7	7.5	7.3	7.0	7.2	7.0	6.8	6.6	6.1	6.0	5.8	5.6	5.1	5.0	4.9	4.7	3.4

