

屋内照明器具特性

品番 (品名)	NNN53820B															
光源	LDA14L-G/K100/W x1 1520.0lm															
管理番号	K0137824(0)DB1															
BZ分類	BZ4															

器具効率	36%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 (X0.01)																ZCM	
下方光束	36%																			
保守率	良 中 否 0.63 0.6 0.56	0.6	21	17	14	12	21	17	14	12	20	16	14	12	19	16	14	12	12	
		0.8	25	21	19	17	24	21	18	17	24	20	18	16	23	20	18	16	16	
		1.0	27	24	21	20	27	24	21	19	26	23	21	19	25	23	21	19	18	
		1.25	30	26	24	22	29	26	24	22	28	26	24	22	27	25	23	22	21	
下方投影面積	cm ²	1.5	31	28	26	24	30	28	26	24	29	27	25	24	28	27	25	24	23	
		2.0	33	31	29	27	32	30	28	27	31	29	28	27	30	29	28	26	26	
取付高さ	器具間隔最大限		2.5	34	32	30	29	33	32	30	29	32	31	30	29	32	30	29	28	27
	横方向 (A)	縦方向 (B)	3.0	35	33	32	30	34	33	31	30	33	32	31	30	32	31	30	29	29
Hm	1.28Hm	1.28Hm	4.0	36	34	33	32	35	34	33	32	34	33	32	32	33	33	32	31	30
			5.0	36	35	34	33	36	35	34	33	35	34	33	33	34	33	33	32	31
			7.0	37	36	35	35	37	36	35	34	36	35	34	34	35	34	34	33	32
			10.0	37	37	36	36	37	37	36	36	36	36	35	35	35	35	35	34	33

