

屋内照明器具特性

品番 (品名)	NNN53820B	
光源	LDA7L-G/D/S/K6 ×1	810.0 lm
管理番号	K0169147(0)DR1	
BZ分類	BZ4	

器具効率	45%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束 下方光束	0% 45%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	2.6	2.1	1.8	1.6	2.6	2.1	1.8	1.6	2.5	2.1	1.8	1.6	2.4	2.0	1.7	1.6	1.5	
		0.8	3.1	2.6	2.3	2.1	3.1	2.6	2.3	2.1	2.9	2.5	2.3	2.1	2.8	2.5	2.2	2.1	2.0	
		1.0	3.4	3.0	2.7	2.4	3.4	2.9	2.7	2.4	3.2	2.9	2.6	2.4	3.1	2.8	2.6	2.4	2.3	
		1.25	3.7	3.3	3.0	2.8	3.6	3.3	3.0	2.8	3.5	3.2	2.9	2.8	3.4	3.1	2.9	2.7	2.6	
下方投影面積 等価発光面積	c m ² c m ²	1.5	3.9	3.5	3.2	3.0	3.8	3.5	3.2	3.0	3.7	3.4	3.2	3.0	3.5	3.3	3.1	3.0	2.9	
		2.0	4.1	3.8	3.6	3.4	4.0	3.8	3.5	3.4	3.9	3.7	3.5	3.3	3.8	3.6	3.4	3.3	3.2	
取付 高さ	器具間隔最大限		2.5	4.2	4.0	3.8	3.6	4.2	3.9	3.8	3.6	4.0	3.9	3.7	3.5	3.9	3.8	3.6	3.5	3.4
	横方向 (A) 縦方向 (B)	3.0	4.3	4.1	3.9	3.8	4.3	4.1	3.9	3.8	4.1	4.0	3.8	3.7	4.0	3.9	3.8	3.7	3.6	
H m	1.29 H m	1.29 H m	4.0	4.4	4.3	4.1	4.0	4.4	4.2	4.1	4.0	4.3	4.1	4.0	3.9	4.2	4.0	4.0	3.9	3.7
			5.0	4.5	4.4	4.3	4.2	4.5	4.3	4.2	4.1	4.3	4.2	4.1	4.1	4.2	4.1	4.1	4.0	3.9
			7.0	4.6	4.5	4.4	4.3	4.5	4.5	4.4	4.3	4.4	4.4	4.3	4.2	4.3	4.3	4.2	4.1	4.0
			10.0	4.7	4.6	4.5	4.5	4.6	4.5	4.5	4.4	4.5	4.4	4.4	4.3	4.4	4.3	4.3	4.3	4.1

