

# 屋内照明器具特性

品番 (品名)	NNN62500														
光源	LDA4L-H-E17/S/4 x1 440.0lm														
管理番号	K0184835(1)DB1														
BZ分類	BZ2														

器具効率	53%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	0%																			
下方光束	53%																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.67	0.6	37	32	28	26	36	31	28	26	35	31	28	26	34	30	28	26	25
		0.63	0.8	41	37	34	31	41	36	33	31	39	36	33	31	38	35	33	31	30
			1.0	44	40	37	35	44	40	37	35	42	39	37	35	41	38	36	34	33
		0.56	1.25	47	43	40	38	46	43	40	38	45	42	40	38	44	41	39	38	37
下方投影面積	c m <sup>2</sup>	1.5	48	45	43	40	48	45	42	40	46	44	42	40	45	43	41	40	39	
		2.0	51	48	46	44	50	47	45	44	49	46	45	43	47	46	44	43	42	
取付高さ	器具間隔最大限		2.5	52	50	48	46	51	49	47	46	50	48	47	45	49	47	46	45	
	横方向 (A)	縦方向 (B)	3.0	53	51	49	48	52	50	49	47	51	49	48	47	50	48	47	46	
H m	1.08H m	1.08H m	4.0	54	52	51	50	53	52	51	49	52	51	50	49	51	50	49	48	
			5.0	55	53	52	51	54	53	52	51	53	52	51	50	51	51	50	49	
			7.0	55	54	54	53	55	54	53	52	54	53	52	51	52	52	51	49	
			10.0	56	55	55	54	55	55	54	54	54	54	53	53	53	53	52	50	

