

# 屋内照明器具特性

品番 (品名)	NNN62500													
光源	LDA5L-G-E17/D/S/K4 ×1      440.0mm													
管理番号	K0184897(1)DB1													
BZ分類	BZ2/2.3/BZ3													

器具効率	54%	天井	80%				70%				50%				30%				0%		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
		床	10%				10%				10%				10%				0%		
上方光束	0%																				
下方光束	54%																				
		室指数	照明率 (X0.01)																	ZCM	
保守率	良 0.67 中 0.63 否 0.56	0.6	36	31	27	25	35	30	27	25	34	30	27	25	33	29	27	25	24		
		0.8	41	36	33	30	40	36	33	30	39	35	32	30	38	35	32	30	29		
		1.0	44	40	37	34	43	39	36	34	42	39	36	34	41	38	36	34	33		
		1.25	47	43	40	38	46	42	40	38	45	42	39	37	44	41	39	37	36		
下方投影面積		1.5	49	45	42	40	48	45	42	40	47	44	42	40	45	43	41	39	38		
等価発光面積		2.0	51	48	46	44	50	48	45	44	49	47	45	43	48	46	44	43	42		
取付高さ	器具間隔最大限		2.5	52	50	48	46	52	49	47	46	50	48	47	45	49	47	46	45	44	
	横方向 (A)	縦方向 (B)	3.0	53	51	49	48	53	51	49	48	51	50	48	47	50	49	47	46	45	
Hm	1.14Hm	1.14Hm	4.0	55	53	51	50	54	52	51	50	52	51	50	49	51	50	49	48	47	
			5.0	55	54	53	52	55	53	52	51	53	52	51	50	52	51	50	50	48	
			7.0	56	55	54	53	55	54	54	53	54	53	53	52	53	52	52	51	50	
			10.0	57	56	55	55	56	55	55	54	55	54	54	53	54	53	53	52	51	

